


1Ch HD Video Passive Balun

PTR-101V-HD+




MODEL		PTR-101V-HD+
Input		1Ch x Twisted Pair
Output		1Ch BNC
System Format		PAL / NTSC
Input Resolution Support		4MP and Lower
Input Signal Support		4 in 1 (AHD / CVI / TVI / CVBS)
Transmission Distance	4MP	200m (AHD) / 150m (CVI / TVI)
	2MP	200m (AHD) / 150m (CVI / TVI)
	1MP	200m (AHD) / 150m (CVI / TVI)
	960H and Lower	200m
Attenuation		1.5db Max
Wiring		Unshielded Twisted Pair
Surge Protection		2KV
Work Environment		-20°C-70°C, 0%-90% Humidity
Power Source		Not Required (Passive Unit)
Dimensions		Camera Side - 51x19x18mm / DVR Side - 40x20x18mm + 140mm Wire
Net Weight		30g

Main Features:

1Ch Set
4MP 4in1 support: AHD / CVI / TVI / CVBS
Passive - No Power Required
Minimal Attenuation
Light Weight

1Ch HD Video + Power Passive Balun

PTR-102VP-HD+



MODEL		PTR-102VP-HD+
Input		1Ch BNC + 12VDC Power
Output		1Ch BNC + 12VDC Power
System Format		PAL / NTSC
Input Resolution Support		4MP and Lower
Input Signal Support		4 in 1 (AHD / CVI / TVI / CVBS)
Transmission Distance	4MP	200m (AHD) / 150m (CVI / TVI)
	2MP	200m (AHD) / 150m (CVI / TVI)
	1MP	200m (AHD) / 150m (CVI / TVI)
	960H and Lower	200m
Attenuation		1.5db Max
Wiring		Cat5/5e/6 crimped cable (RJ-45)
Surge Protection		2KV
Work Environment		-20°C-70°C, 0%-90% Humidity
Power Source		Not Required (Passive Unit). Power is required for powered device only.
Dimensions		Camera/DVR Side - 73x29x20mm + 113mm Wire
Net Weight		60g

Main Features:

1Ch Set
4MP 4in1 support: AHD / CVI / TVI / CVBS
Passive
Minimal Attenuation
Light Weight

Power transmission max. distance

Model Power Supply Consumption	DC 12V	DC 15V
200mA	180m	280m
300mA	120m	180m
400mA	100m	130m
500mA	80m	110m
600mA	60m	90m