

[PRODUCTOS](#)[SOPORTE](#)[CORPORATIVO](#)[DÓNDE COMPRAR](#)[Search All](#)[Global](#)[Routers](#) | **MW302R**[Descripción General](#)[Especificaciones](#)

Ethernet Ports	2*10/100Mbps LAN Ports & 1*10/100Mbps WAN Port
Button	Reset Button
External Power Supply	5V/0.6A
Dimensions (W X D X H)	114 mm × 94 mm × 26 mm
Antenna Type	2 * 5dBi
Package Contents	300Mbps Wireless N Router (MW302R) Power Adapter Quick Installation Guide Ethernet Cable
Wireless Standards	IEEE 802.11b/g/n
Frequency	2.4-2.4835GHz
Signal Rate	<ul style="list-style-type: none"> • 11n: Up to 300Mbps (Dynamic) • 11g: Up to 54Mbps (Dynamic) • 11b: Up to 11Mbps (Dynamic)
Reception Sensitivity	<ul style="list-style-type: none"> • 270M: -73dBm@10% PER • 130M: -75dBm@10% PER • 54M: -77dBm@10% PER • 11M: -90dBm@10% PER • 6 M: -94dBm@10% PER • 1 M: -96dBm@10% PER
Wireless Functions	Enable/Disable Wireless Radio, WDS Bridging
Wireless Security	WPA-PSK / WPA2-PSK
WAN Type	Dynamic IP/Static IP/PPPoE/PPTP/L2TP
DHCP	Server
Port Forwarding	Virtual Server, UPnP, DMZ
Management	Access Control, Local Management, Remote Management
Firewall Security	IP and MAC Address Binding
Guest Network	2.4GHz Guest Network
Protocols	IPv4, IPv6

Environment

- Operating Temperature: 0°C~40°C (32°F~104°F)
- Storage Temperature: -40°C~70°C (-40°F~158°F)
- Operating Humidity: 10%~90% Non-Condensing
- Storage Humidity: 5%~90% Non-Condensing

Transmission Power

<20dBm (EIRP)

Copyright © 2020 MERCUSYS Technologies Co., Ltd. All rights reserved.