

Overview

Aruba 570 Series Outdoor Access Points

High-performance Wi-Fi 6 (802.11ax) for outdoor and hazardous location environments

Weatherproof and temperature-hardened, Aruba 570 Series access points deliver the highest Wi-Fi 6 performance in outdoor and environmentally challenging locations. The 570 high-performance and high power series deliver maximum capacity and range. It delivers 4x4:4SS MU-MIMO capability, Aruba's advanced ClientMatch and integrated Bluetooth to enable Aruba location services.

Purpose-built to survive in the harshest outdoor environments, 570 Series APs withstand exposure to extreme high and low temperatures, persistent moisture and precipitation, and are fully sealed to keep out airborne contaminants. All electrical interfaces include industrial strength surge protection.

Aruba Wi-Fi 6 access points provide high-performance connectivity for any organization experiencing growing numbers of IoT and mobility requirements. With a maximum aggregate on-air data rate of 3 Gbps (HE80/HE40) they deliver the speed and reliability needed for any environment.



Standard Features

Incredible Efficiency

The 570 Series APs are also designed to optimize user experience by maximizing Wi-Fi efficiency and dramatically reducing airtime contention between clients.

Features include Uplink and Downlink Orthogonal Frequency Division Multiple Access (OFDMA), Downlink Multi-User MIMO (MU MIMO) and cellular co-location. With up to 4 spatial stream and 160 MHz channel capability the 570 Series provides groundbreaking wireless capabilities for any application.

Read the [Multi-User 802.11ax white paper](#) for further information.

Advantages of OFDMA

This capability allows Aruba Wi-Fi 6 APs to handle multiple Wi-Fi 6 enabled client simultaneously on a single radio.

Channel utilization is optimized by handling each transaction by matching allocated bandwidth in a channel to the offered user load. These sub divisions of the channel are referred to as Resource Units (RU).

Aruba AirSlice™ for Extended OFDMA Assurance

Initially, APs in controller-less mode (Instant) can provide SLA- grade performance by allocating RUs to specific traffic types.

By combining Aruba's Policy Enforcement Firewall (PEF) and Layer 7 deep packet inspection (DPI) to identify user roles and applications, the APs will dynamically allocate the bandwidth needed. Non-Wi-Fi 6 clients can also benefit.

Multi-User MIMO (MU-MIMO)

The 570 Series APs support downlink MU-MIMO similar to Wi-Fi 5 (802.11ac Wave 2) APs. With the introduction OFDMA in Wi-Fi 6 the overhead for this capability is reduced and MU-MIMO effectiveness is substantially improved for large client counts.

Wi-Fi 6 and MU-MIMO aware client optimization

Aruba's patented AI-powered ClientMatch technology ensures that all clients are attached to their best-serving access point. Session metrics, network metrics, applications, client type, are used to identify and maintain best connection.

Aruba Advanced Cellular Coexistence (ACC)

This features uses built-in filtering to automatically minimize the impact of interference of high-power cellular base stations, in building distributed antenna systems as well as small cell and femtocell equipment.

Intelligent Power Monitoring (IPM)

Aruba APs continuously monitor and report hardware energy consumption. APs can be configured to enable or disable capabilities based on the available PoE power - ideal when wired switches have exhausted their power budget.

Green AP energy efficiency

Aruba Wi-Fi 6 APs utilize AI-powered analytics to automatically transition in and out of a sleep mode.

Standard Features

IoT Platform Capabilities

Aruba Wi-Fi 6 APs include an integrated Bluetooth 5 and 802.15.4 radio (for Zigbee support) to simplify deploying and managing IoT-based location services, asset tracking services, security solutions and IoT sensors. This allows organizations to leverage the 570 Series as an IoT platform, which eliminates the need for an overlay infrastructure and additional IT resources.

Target Wake Time (TWT)

Ideal for IoT solutions that communicate infrequently, this Wi-Fi 6 capability allows IoT devices to use 802.11ax protocol. TWT coordinates with client devices to allow them to sleep for extended periods and use shorter wake times to communicate before returning to sleep. This substantially extends the useful operating life of Wi-Fi 6 based battery powered sensors.

Aruba Secure Infrastructure

The Aruba 570 Series is an integral part of Aruba's 360 Secure Fabric to help protect user authentication and wireless traffic.

WPA2-MPSK

MPSK enables simpler passkey management for WPA2 devices - should the Wi-Fi password on one device change, no additional changes are needed for other devices. This feature is enabled when networks are deployed with ClearPass Policy Manager.

VPN Tunnels

In Remote AP (RAP) and IAP-VPN deployments, the Aruba 570 Series can be used to establish a secure SSL/IPSec VPN tunnel to a Mobility Controller that is configured as a VPN concentrator.

Trusted Platform Module (TPM)

For enhanced device assurance, all Aruba APs have an installed TPM for secure storage of credentials, keys and boot code.

Simple and Secure Access

To simplify policy enforcement, the Aruba 570 Series uses Aruba's policy enforcement firewall (PEF) features to encapsulate all traffic from the AP to the Mobility Controller (Gateway) for end-to-end encryption and inspection. Policies are applied based on context including: user role, device type, application, and location. This reduces the manual configuration of SSIDs, VLANs, and ACLs. PEF also serves as the underlying technology for [Aruba Dynamic Segmentation](#).

High-Density Connectivity

Each 570 Series AP provides connectivity for a maximum of 512 associated clients per radio (1024 total).

Flexible Operation and Management

A unique feature of Aruba APs is the ability to operate in either controller-less or controller-based mode.

Standard Features

Controller-less (Instant) Mode

In controller-less mode, one AP serves as a virtual controller for the entire network. Learn more about Instant mode in this [technology brief](#).

Mobility Controller Mode

For optimized network performance, roaming and security, APs tunnel all traffic to a mobility controller for central management of traffic forwarding, segmentation, encryption, and policy enforcement. Learn more in the ArubaOS datasheet.

Management Options

Available management solutions include Aruba Central, cloud based, or Aruba AirWave, a multi-vendor, on-premises, management solution.

For large installations across multiple sites, Aruba APs can be shipped and activated with Zero Touch Provisioning through Aruba Central or Airwave. This reduces deployment time, centralizes configuration, and provides inventory visibility.

Additional Wi-Fi Features

- Transmit Beamforming (TxBF)
 - Increased signal reliability and range
 - Passpoint Release 2
 - Seamless cellular-to-Wi-Fi carryover for guests
 - Dynamic Frequency Selection (DFS)
 - Optimized use of available RF spectrum
 - Maximal Ratio Combining (MRC)
 - Improved receiver performance for multi antenna access points
 - Cyclic Delay/Shift Diversity (CDD/CSD)
 - Enable use of multiple transmit antennas
 - Space-Time Block Coding (STBC)
 - Increased connection robustness
 - Low-Density Parity Check (LDPC)
 - High performance error detection and correction coding for enhanced receiver performance.
-

Configuration Information

BTO Models

Remark Description

SKU

s

570 Unified Outdoor Access Points

Aruba AP-574 (RW) 802.11ax 2x2:2/4x4:4 Dual Radio 6xNf Connectorized Outdoor AP	R4H12A
Aruba AP-574 (US) 802.11ax 2x2:2/4x4:4 Dual Radio 6xNf Connectorized Outdoor AP	R4H13A
Aruba AP-574 (EG) 802.11ax 2x2:2/4x4:4 Dual Radio 6xNf Connectorized Outdoor AP	R4H09A
Aruba AP-574 (IL) 802.11ax 2x2:2/4x4:4 Dual Radio 6xNf Connectorized Outdoor AP	R4H10A
Aruba AP-574 (JP) 802.11ax 2x2:2/4x4:4 Dual Radio 6xNf Connectorized Outdoor AP	R4H11A
Aruba AP-575 (RW) 802.11ax 2x2:2/4x4:4 Dual Radio Integrated Omni Antenna Outdoor AP	R4H17A
Aruba AP-575 (US) 802.11ax 2x2:2/4x4:4 Dual Radio Integrated Omni Antenna Outdoor AP	R4H18A
Aruba AP-575 (EG) 802.11ax 2x2:2/4x4:4 Dual Radio Integrated Omni Antenna Outdoor AP	R4H14A
Aruba AP-575 (IL) 802.11ax 2x2:2/4x4:4 Dual Radio Integrated Omni Antenna Outdoor AP	R4H15A
Aruba AP-575 (JP) 802.11ax 2x2:2/4x4:4 Dual Radio Integrated Omni Antenna Outdoor AP	R4H16A
Aruba AP-577 (RW) 802.11ax 2x2:2/4x4:4 Dual Radio Integrated Directional Antenna Outdoor AP	R4H22A
Aruba AP-577 (US) 802.11ax 2x2:2/4x4:4 Dual Radio Integrated Directional Antenna Outdoor AP	R4H23A
Aruba AP-577 (EG) 802.11ax 2x2:2/4x4:4 Dual Radio Integrated Directional Antenna Outdoor AP	R4H19A
Aruba AP-577 (IL) 802.11ax 2x2:2/4x4:4 Dual Radio Integrated Directional Antenna Outdoor AP	R4H20A
Aruba AP-577 (JP) 802.11ax 2x2:2/4x4:4 Dual Radio Integrated Directional Antenna Outdoor AP	R4H21A

570 TAA Unified Outdoor Access Points

Aruba AP-574 (RW) TAA 802.11ax 2x2:2/4x4:4 Dual Radio 6xNf Connectorized Outdoor AP	R4H27A
Aruba AP-574 (US) TAA 802.11ax 2x2:2/4x4:4 Dual Radio 6xNf Connectorized Outdoor AP	R4H28A
Aruba AP-574 (EG) TAA 802.11ax 2x2:2/4x4:4 Dual Radio 6xNf Connectorized Outdoor AP	R4H24A
Aruba AP-574 (IL) TAA 802.11ax 2x2:2/4x4:4 Dual Radio 6xNf Connectorized Outdoor AP	R4H25A
Aruba AP-574 (JP) TAA 802.11ax 2x2:2/4x4:4 Dual Radio 6xNf Connectorized Outdoor AP	R4H26A
Aruba AP-575 (RW) TAA 802.11ax 2x2:2/4x4:4 Dual Radio Integrated Omni Antenna Outdoor AP	R4H32A

Configuration Information

Aruba AP-575 (US) TAA 802.11ax 2x2:2/4x4:4 Dual Radio Integrated Omni Antenna Outdoor AP	R4H33A
Aruba AP-575 (EG) TAA 802.11ax 2x2:2/4x4:4 Dual Radio Integrated Omni Antenna Outdoor AP	R4H29A
Aruba AP-575 (IL) TAA 802.11ax 2x2:2/4x4:4 Dual Radio Integrated Omni Antenna Outdoor AP	R4H30A
Aruba AP-575 (JP) TAA 802.11ax 2x2:2/4x4:4 Dual Radio Integrated Omni Antenna Outdoor AP	R4H31A
Aruba AP-577 (RW) TAA 802.11ax 2x2:2/4x4:4 Dual Radio Integ Directional Antenna Outdoor AP	R4H37A
Aruba AP-577 (US) TAA 802.11ax 2x2:2/4x4:4 Dual Radio Integ Directional Antenna Outdoor AP	R4H38A
Aruba AP-577 (EG) TAA 802.11ax 2x2:2/4x4:4 Dual Radio Integ Directional Antenna Outdoor AP	R4H34A
Aruba AP-577 (IL) TAA 802.11ax 2x2:2/4x4:4 Dual Radio Integ Directional Antenna Outdoor AP	R4H35A
Aruba AP-577 (JP) TAA 802.11ax 2x2:2/4x4:4 Dual Radio Integ Directional Antenna Outdoor AP	R4H36A

Notes: [OCA Only Model Selection Form - Aruba > Wireless > Access Points > Outdoor / Rugged: Aruba 570 Series Access Points](#)

Mounting Accessories

Remark Description

SKU

s

AP Mount Kits

For 574, 575, 577 Std (Min 0 // max 1) User Selection (min 0 // max 1)

AP-270-MNT-V1 AP-270 Series Outdoor Pole/Wall Long Mount Kit JW052A

AP-270-MNT-V2 AP-270 Series Outdoor Pole/Wall Short Mount Kit JW053A

AP-270-MNT-H1 AP-270 Series Outdoor AP Hanging or Tilt Install Mount Kit JW054A

AP-270-MNT-H2 AP-270 Series Access Flush Wall or Ceiling Mount JW055A

AP-270-MNT-H3 AP-270 Series Outdoor AP Hanging or Dual-Tilt Install Mount Kit R6W11A

Notes: **For 574:**

V2 bracket most often with AP-574. Leaves chassis 7.5 cm (3") from mounting asset

H1 bracket most often used for hanging from inclined or horizontal structure.

The AP-37x chassis does not ship with bracket.

For 575:

V1 bracket most often used for pole mount.

V2 bracket most often used for wall mount.

H1 bracket most often used for hanging from inclined or horizontal structure.

The AP-37x chassis does not ship with bracket

For 577:

H1 bracket most often with AP-577 for mounting to a wall. Allows chassis tilt.

V1 and V2 brackets can be used but will result in the AP-577 pointing down.

The AP-37x chassis does not ship with bracket.

Configuration Information

Power Options

Rule #	Description	SKU
	PoE Power Options	
	For 574, 575, 577 Std (Min 0 // max 1) User Selection (min 0 // max 1)	
	PD-9501-5GCO-AC 60W 802.3bt Smart Rate Outdoor Surge Protection Midspan Injector	R7T40A
	PD-9501-5GCO-DC 60W 802.3bt Smart Rate Outdoor Surge Protection Midspan Injector	R7T41A
*	AP-POE-ATSR 1-Port Smart Rate 802.3at 30W midspan injector	R6P67A
*	AP-POE-BTSR 1-Port Smart Rate 802.3bt 60W midspan injector	R1C73A
Notes:	<p>*If this Power Injector is selected, bring in (Min 1 // Max 1) Localized power cord based on the Aruba Localization Menu</p> <p>Indoor Injector provides no surge protection</p> <p>Indoor injector requires indoor AC power cord x </p> <p>AP-57X may be powered by PoE Only</p> <p>Power Cord for JW630A, R7T40A, R7T41A should be provided by installer</p> <p>R7T40A and R7T41A do not include a power cord, power cord must be constructed by installer using the included power connector parts and assembled per the user guide by a certified installer</p>	
	Power Injector Mounts	
	For 574, 575, 577 Std (Min 0 // max 1) User Selection (min 0 // max 1)	
	Aruba PD-MOUNT-OD Outdoor PoE Midspan Injectors Pole/Mast Mount Kit	JW620A
Notes:	This is optional but recommended for outdoor injectors	

Antennas

Remark	Description	SKU
s		
	5.0 GHz Antennas	
	For 574 Std (Min 0 // max 4) User Selection (min 0 // max 4)	
*	ANT-2x2-5005 Pair 5GHz 5dBi Omni N-type Direct Mount Outdoor Antennas	JW026A
*	ANT-2x2-5010 Pair 5GHz 10dBi Omni N-Type Direct Mount Outdoor Antennas	JW027A
	ANT-4x4-5314 5.15-5.9GHz 14dBi 30x30deg Dual Pol MIMO Hi Gain Dir N-Type Outdoor Antenna	JX988A
	ANT-3x3-5712 4.9-5.9GHz 12.0dBi 75x25deg +/- 45deg and V Pol 3 MIMO High Gain Dir Antenna	JW033A
	ANT-4x4-D707 Dual-Band 70x50deg 7dBi Panel V/H/+/-45 4 Element MIMO Outdoor Antenna	S0A65A
Notes:	<p>*Must select Qty 0 or Qty 2</p> <p>All antennas defined for AP-574 ship with bracket</p> <p>ANT-2x2-5005, ANT-2x2-5010 are usually direct connect</p> <p>Radio 0 (5.0 GHz) has 4 connectors</p> <p>Other antennas are N-type female connectorized</p>	
	2.4 GHz Antennas	
	For 574 Std (Min 0 // max 2) User Selection (min 0 // max 2)	
	ANT-2x2-2005 Pair 2.4GHz 5dBi Omni N-type Direct Mount Outdoor Antennas	JW023A
	ANT-2x2-2314 2.4 GHz 14dBi 30x30deg Dual Pol MIMO High Gain Dir N-Type Outdoor Antenna	JW024A
	ANT-2x2-2714 2.4G 14dBi 70deg Sector Dual Pol MIMO N-type Outdoor Antenna	JW025A
	ANT-3x3-D608 Dual Band 60x60deg 8dBi +/- 45 and Vert Pol MIMO N-Type Antenna	JW035A

Configuration Information

ANT-4x4-D707 Dual-Band 70x50deg 7dBi Panel V/H/+/-45 4 Element MIMO Outdoor Antenna S0A65A

- Notes:** All antennas defined for AP-574 ship with bracket
 ANT-2x2-2005 is usually direct connect
 ANT-4X4-D707 on 2.4Ghz radios will only use 2 connectors
 Radio 1 (2.4 GHz) has 2 connectors
 Other antennas are N-type female connectorized

Cables

RF Cables

For 574 Std (Min 0 // max 6) User Selection (min 0 // max 6)

AP-CBL-1 10ft(3m) Nm to Nf Outdoor Rated RF Cable	JW070A
ANT-CBL-1 1m Nm to Nm Flexible Outdoor Rated RF Cable	JW068A
ANT-CBL-2 2m Nm to Nm Flexible Outdoor Rated RF Cable	JW069A
AFC7DL03-00 3m Nm to Nm Outdoor Rated RF Cable	JW064A
AFC7DL04-00 4m Nm to Nm Outdoor Rated RF Cable	JW065A

- Notes:** AP-CBL-1 (JW070A) is an RF extension cable only
 Radio 0 has 4 connectors
 Radio 1 has 2 connectors
 No cables required for direct connect omnis

Accessories

Remark	Description	SKU
s		

Lightning Surge Arrestor

For 574 Std (Min 0 // max 6) User Selection (min 0 // max 6)

AP-LAR-1 Nm to Nf Outdoor DC to 6 GHz In-line Coaxial Lightning Arrestor	JW061A
--	--------

- Notes:** Not required unless RF cables are longer than 2m in length
 When used these are ordered in groups of 4 for the 5Ghz radio
 When used these are ordered in groups of 2 for the 2.4Ghz radio

Installation Materials

For 574 Std (Min 0 // max 1) User Selection (min 0 // max 1)

AINS2KKIT-00 2 Elec Tape Rolls Mastic Tape and White Tie Wraps Otdr Install Materials	JW063A
---	--------

- Notes:** Not normally required for any connections at the chassis

Spare Items

Std (Min 0 // max 99) User Selection (min 0 // max 99)

Outdoor AP Covers and Glands 1-pk M25/5-pk M20 Cover/2-pk M16 Cover/5-pk M20 Gland/2-pk Ground Kit	Q8N47A
--	--------

- Notes:** This is a collection of extra covers and cabling glands, replicating what is in the shipping box

Outdoor AP Metric to Standard M20 to 1/2 inch NPT 5-pk Thread Adapter	Q8N48A
---	--------

- Notes:** This is a thread adapter normally used to allow direct interface for 1/2" NPT conduit

Configuration Information

Software

Remark	Description	SKU
--------	-------------	-----

s

	Aruba Central AP Foundation 1 year Subscription E-STU	Q9Y58AAE
	Aruba Central AP Foundation 3 year Subscription E-STU	Q9Y59AAE
	Aruba Central AP Foundation 5 year Subscription E-STU	Q9Y60AAE
	Aruba Central AP Foundation 7 year Subscription E-STU	Q9Y61AAE
	Aruba Central AP Foundation 10 year Subscription E-STU	Q9Y62AAE
	Aruba Central AP Advanced 1yr Subscription E-STU	Q9Y63AAE
	Aruba Central AP Advanced 3yr Subscription E-STU	Q9Y64AAE
	Aruba Central AP Advanced 5yr Subscription E-STU	Q9Y65AAE
	Aruba Central AP Advanced 7yr Subscription E-STU	Q9Y66AAE
	Aruba Central AP Advanced 10yr Subscription E-STU	Q9Y67AAE

Notes: [Add the Central Cloud Skus to the Aruba Catalog as Standalone:](#)
[Aruba > Network Management > Central > Cloud Services](#)

	Aruba Central On-Premises AP Foundation 1 year Subscription E-STU	R6U63AAE
	Aruba Central On-Premises AP Foundation 3 year Subscription E-STU	R6U64AAE
	Aruba Central On-Premises AP Foundation 5 year Subscription E-STU	R6U65AAE
	Aruba Central On-Premises AP Foundation 7 year Subscription E-STU	R6U66AAE
	Aruba Central On-Premises AP Foundation 10 year Subscription E-STU	R6U67AAE

Notes: [Add the Central On-Prem Skus to the Aruba Catalog as Standalone:](#)
[Aruba > Network Management > Central > On-Prem Services](#)

Technical Specifications

Wi-Fi Radio Specifications

- AP type: Outdoor- hardened, Wi-Fi 6 dual-radio, 5 GHz 4x4 MIMO and 2.4 GHz 2x2 MIMO
- Software-configurable dual radio supports 5 GHz (Radio 0) and 2.4 GHz (Radio 1)

5 GHz

- Four spatial stream Single User (SU) MIMO for up to 4.8 Gbps wireless data rate to individual 4SS HE160 Wi-Fi 6 client device (max)
- Two spatial stream Single User (SU) MIMO for up to 1.2 Gbps wireless data rate to individual 2SS HE80 Wi-Fi 6 client device (typical)
- Four spatial stream Multi User (MU) MIMO for up to 4.8 Gbps wireless data rate to up to four 1SS or two 2SS HE160 Wi-Fi 6 DL-MU-MIMO capable client devices simultaneously (max)
- Four spatial stream Multi User (MU) MIMO for up to 2.4 Gbps wireless data rate to up to four 1SS or two 2SS HE80 Wi-Fi 6 DL-MU-MIMO capable client devices simultaneously (typical)

2.4 GHz

- Two spatial stream Single User (SU) MIMO for up to 575 Mbps wireless data rate to individual 2SS HE40 Wi-Fi 6 client device (max)
- Two spatial stream Single User (SU) MIMO for up to 287 Mbps wireless data rate to individual 2SS HE20 Wi-Fi 6 client device (typical)
- Two spatial stream Multi User (MU) MIMO for up to 575 Mbps wireless data rate to up to two 1SS HE40 Wi-Fi 6 DL- MU-MIMO capable client devices simultaneously (max)
- Two spatial stream Multi User (MU) MIMO for up to 287 Mbps wireless data rate to up to two 1SS HE20 Wi-Fi 6 DL- MU-MIMO capable client devices simultaneously (typical)
- Support for up to 512 associated client devices per radio, and up to 16 BSSIDs per radio
- Supported frequency bands (country-specific restrictions apply):
 - 2.400 to 2.4835 GHz
 - 5.150 to 5.250 GHz
 - 5.250 to 5.350 GHz
 - 5.470 to 5.725 GHz
 - 5.725 to 5.850 GHz
 - 5.850 to 5.925 GHz
 - 5.825 to 5.875 GHz
- Available channels: Dependent on configured regulatory domain
- Dynamic frequency selection (DFS) optimizes the use of available RF spectrum
- Supported radio technologies:
 - 802.11b: Direct-sequence spread-spectrum (DSSS)
 - 802.11a/g/n/ac: Orthogonal frequency-division multiplexing (OFDM)
 - 802.11ax: Orthogonal frequency-division multiple access (OFDMA) with up to 16 resource units (RU)
- Supported modulation types:
 - 802.11b: BPSK, QPSK, CCK
 - 802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM (proprietary extension)
 - 802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM, 1024 QAM (proprietary extension)
 - 802.11ax: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM , 1024 QAM
 - 802.11n high-throughput (HT) support: HT 20/40
 - 802.11ac very high throughput (VHT) support: VHT 20/40/80/160
 - 802.11ax high efficiency (HE) support: HE20/40/80/160
- Supported data rates (Mbps):
 - 802.11b: 1, 2, 5.5, 11
 - 802.11a/g: 6, 9, 12, 18, 24, 36, 48, 54

Technical Specifications

- 802.11n (2.4GHz): 6.5 to 300 (MCS0 to MCS15, HT20 to HT40)
- 802.11n (5GHz): 6.5 to 600 (MCS0 to MCS31, HT20 to HT40)
- 802.11ac: (5 GHz): 6.5 to 3,467 (MCS0 to MCS9, NSS = 1 to 4 for VHT20 to VHT160)
- 802.11ax (2.4GHz): 3.6 to 574 (MCS0 to MCS11, NSS = 1 to 2, HE20 to HE40)
- 802.11ax (5GHz): 3.6 to 4803 (MCS0 to MCS11, NSS = 1 to 4, HE20 to HE160)
- 802.11n/ac packet aggregation: A-MPDU, A-MSDU
- Transmit power: Configurable in increments of 0.5 dBm
- Maximum (conducted) transmit power (limited by local regulatory requirements):
- 2.4 GHz band: +22 dBm per chain , +25dBm aggregate (2x2)
- 5 GHz band: +22 dBm per chain , +28dBm aggregate (4x4)
- **Notes: Conducted transmit power levels exclude antenna gain**
- Maximum EIRP (limited by local regulatory requirements):
- 2.4 GHz band:
- AP-574: 25 + antenna gain + TxBF gain
- AP-575: 29.0 dBm EIRP
- AP-577: 34.4 dBm EIRP
- 5 GHz band:
- AP-574: 28 + antenna gain + TxBF gain
- AP-575: 32.6 dBm EIRP
- AP-577: 36 dBm EIRP
- Advanced Cellular Coexistence (ACC) minimizes interference from cellular networks
- Maximum ratio combining (MRC) for improved receiver performance
- Cyclic delay/shift diversity (CDD/CSD) to enable the use of multiple transmit antennas
- Short guard interval for 20-MHz, 40-MHz, 80-MHz and 160-MHz channels
- Space-time block coding (STBC) for increased range and improved reception
- Low-density parity check (LDPC) for high-efficiency error correction and increased throughput
- Transmit beam-forming (TxBF) for increased signal reliability and range

Aruba 570 Series Specifications

- AP-574
- 5 GHz: Four Nf connectors for external antenna operation
- 2.4 GHz Two Nf connectors for external antenna operation
- AP-575
- Built-in omni-directional antennas
- 5 GHz Antennas 4.6 dBi
- 2.4 GHz Antennas 4.0 dBi
- AP-577
- Built-in 90°H x 90°V directional antennas
- 5 GHz Antennas 6.3 dBi
- 2.4 GHz Antennas 6.4 dBi

Power

- Worst-case power consumption from the AP: 25.6W
- Power sources sold separately
- Power over Ethernet (PoE+): 802.3at-compliant

Mounting

Technical Specifications

- Optional mounting kits:
 - AP-270-MNT-V1
 - AP-270-MNT-V2
 - AP-270-MNT-H1
 - AP-270-MNT-H2
-

Additional interfaces

- E0: HPE SmartRate port (RJ-45)
 - Auto-sensing link speed (100/1000/2500BASE-T) and MDI/MDX
 - 2.5Gbps speed complies with NBase-T and 802.3bz specifications
 - PoE-PD: 48Vdc (nominal) 802.3af/at/bt (Class 3 or higher)
 - 802.3az Energy Efficient Ethernet (EEE)
 - E1: 10/100/1000BASE-T (RJ-45)
 - Auto-sensing link speed and MDI/MDX
 - 802.3az Energy Efficient Ethernet (EEE)
 - Link Aggregation (LACP) support between both network ports for redundancy and increased capacity
 - Bluetooth 5 and 802.15.4 radio
 - 2.4 GHz
 - Bluetooth 5: up to 8dBm transmit power and -95dBm receive sensitivity
 - Zigbee: up to 8 dBm transmit power and -97dBm receive sensitivity
 - Up to 4dBm transmit power (class 2) and -91 dBm receive sensitivity
 - Visual indicator (multi-color LED): For system and radio status
 - Reset button: Factory reset (during device power up)
 - USB-C console interface
-

Dimensions and weight

- Dimensions and weights exclude mount
 - AP-574:
 - 23 (W) x 24 (D) x 19 cm (H)
 - 9.0 (W) x 9.4 (D) x 7.5 in (H)
 - 2.4 kg/5.3 lbs
 - AP-575:
 - 23 (W) x 24 (D) x 27 cm (H)
 - 9.0 (W) x 9.4 (D) x 10.6 in (H)
 - 2.4 kg/5.3 lbs
 - AP-577:
 - 23 (W) x 22 (D) x 13 cm (H)
 - 9.0 (W) x 8.7 (D) x 5.1 in (H)
 - 2.1 kg/4.6 lbs
-

Environmental

- Operating:
 - Temperature: -40° C to +65° C (-40° F to +149° F)
 - Humidity: 5% to 95% non-condensing internal to chassis.
 - Storage and transportation:
 - Temperature: -40° C to +70° C (-40° F to +158° F)
-

Technical Specifications

- Operating altitude: 3,000 m
 - Water and dust: IP66/67
 - Salt tolerance: tested to ASTM B117-07A salt spray 200hrs
 - Wind survival: up to 165 Mph
 - Shock and vibration: ETSI 300-19-2-4
-

Regulatory

- FCC/ISED
 - CE Marked
 - RED Directive 2014/53/EU
 - EMC Directive 2014/30/EU
 - Low Voltage Directive 2014/35/EU
 - UL/IEC/EN 60950
 - EN 60601-1-1, EN60601-1-2
 - For more country-specific regulatory information and approvals, please see your Aruba representative.
-

Regulatory Model Numbers

- AP-574: APEX0574
 - AP-575: APEX0575
 - AP-577: APEX0577
-

Certifications

- CB Scheme Safety, cTUVus
 - UL2043 plenum rating
 - Wi-Fi Alliance certified 802.11a/b/g/n
 - Wi-Fi CERTIFIED™ 6 (802.11ax)
 - Wi-Fi CERTIFIED™ ac (with Wave 2 features)
 - Passpoint® (Release 2) with ArubaOS and Instant
-

Warranty

- Limited lifetime warranty
-

Minimum Operating System Software

- ArubaOS and Aruba InstantOS 8.7.0.0
-

Technical Specifications

RF Performance Table		
	Maximum transmit power (dBm) per transmit chain	Receiver sensitivity (dBm) per receive chain
2.4 GHz, 802.11b		
1 Mbps	22	-97
11 Mbps	22	-89
2.4 GHz, 802.11g		
6 Mbps	22	-94
54 Mbps	20	-76
2.4 GHz, 802.11n/ac HT20		
MCS0	22	-93
MCS8	19	-72
2.4 GHz, 802.11ax HE20		
MCS0	22	-93
MCS11	17	-62
5 GHz, 802.11a		
6 Mbps	22	-95
54 Mbps	20	-76
5GHz, 802.11n/ac HT20/VHT20		
MCS0	22	-94
MCS8	19	-72
5GHz, 802.11n/ac HT40/VHT40		
MCS0	22	-92
MCS9	19	-68
5GHz, 802.11ac VHT80		
MCS0	22	-90
MCS9	19	-65
5GHz, 802.11ac VHT160		
MCS0	22	-84
MCS9	19	-59
5GHz, 802.11ax HE20		
MCS0	22	-94
MCS11	17	-62
5GHz, 802.11ax HE40		
MCS0	22	-91
MCS11	17	-60
5GHz, 802.11ax HE80		
MCS0	22	-87
MCS11	17	-57
5GHz, 802.11ax HE160		
MCS0	22	-85
MCS11	17	-53



Notes: Maximum capability of the hardware provided (excluding antenna gain). Maximum transmit power is limited by local regulatory settings.

Summary of Changes

Date	Version History	Action	Description of Change
01-Aug-2022	Version 6	Changed	Configuration Information section was updated.
06-Dec-2021	Version 5	Changed	SKUs were added in Configuration Information section
15-Mar-2021	Version 4	Changed	SKUs were added in Configuration Information section
02-Nov-2020	Version 3	Changed	Configuration Information section was updated. New SKUs were added.
08-Sep-2020	Version 2	Changed	Configuration Information section was updated. New SKUs were added.
04-May-2020	Version 1	New	New QuickSpecs

Copyright

Make the right purchase decision. Contact our presales specialists.



© Copyright 2022 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

To learn more, visit: <http://www.hpe.com/networking>

a00056659enw - 16341 - Worldwide - V6 - 01-August-2022

