

Overview

HPE 16Gb Fibre Channel Host Bus Adapter

The HPE 16Gb Host Bus Adapters are designed to support ProLiant Servers with PCI-Express I/O slots to connect to Hewlett Packard Enterprise Storage Arrays using the 16/8/4 Gb Fibre Channel protocol. The HPE 16Gb Host Bus Adapters bring datacenter infrastructure components to a higher level of performance and efficiency with the ability to deliver twice the I/O performance of 8Gb HBAs at lower latency. A 16Gb FC HBA purchased today is backward compatible with 8 Gb and 4 Gb storage networks and will protect future investments. When using storage intensive applications, such as backup/restore, database transactions, virtualization, and rich media, the increased performance of the 16 Gb infrastructure enables more rapid storage and retrieval of critical information. Designed for environments with greater virtual machine density and bandwidth requirements, the 16Gb HBAs enable more applications and VMs to run on a single host server and Fibre Channel port, resulting in reduced cabling and a higher return on IT investment. The four port adapters are specially designed for PCIe slot constrained servers which run workloads that demand extremely high storage networking bandwidth.

What's New

- FC-NVMe support in Windows, VMware and Linux OSes

Models

Description	SKU
Single Port	
SN1200E Single Port	
HPE SN1200E 16Gb Single Port Fibre Channel Host Bus Adapter	Q0L13A
SN1100Q Single Port	
HPE SN1100Q 16Gb Single Port Fibre Channel Host Bus Adapter	P9D93A
Dual Port	
SN1200E Dual Port	
HPE SN1200E 16Gb Dual Port Fibre Channel Host Bus Adapter	Q0L14A
SN1100Q Dual Port	
HPE SN1100Q 16Gb Dual Port Fibre Channel Host Bus Adapter	P9D94A

Standard Features

Key Features and Benefits

Performance

Delivers, up to three times the IOPS*, twice the data throughput (MB/s) and cuts latency by half compared to 8Gb FC HBAs

Best Fibre Channel IOPS, latency and throughput performance enables increased application and database transactions per second, enables faster large block transfers and increases the number of VMs that can be supported per server.

Notes: * The HPE SN1200E delivers up to 1.6 million IOPS on a single port or in aggregate across both ports

Support for greater Server Virtualization

Ideal for high density server virtualization environments

Enables more applications and VMs to run on a single server and Fibre Channel port, resulting in reduced cabling and a higher return on IT investment.

Provides HPE ProLiant Connectivity to HPE Storage And Network

Robust interoperability testing

- Provides an HPE-branded HBA solution which has undergone extensive HPE interoperability testing for connecting HPE ProLiant servers into HPE Storage and networking environments.
 - Optimal for connecting to The HPE 16Gb FC edge/core network switches.
-

Smart SAN support

Smart SAN is a protocol agnostic application embedded in SAN components that enables SCSI-attached Alletra/Primera/3PAR to orchestrate configuration, settings and policies in a SAN. HPE Smart SAN's Target Driven Zoning enables you to configure zones accurately in minutes and not in hours and its automatic discovery mechanism creates a powerful platform which would enable real-time diagnostics with self-healing in the near future.

Express Lane prioritization

The SN1200E enables I/O prioritization of physical or virtual server to a LUN or a group of LUNs ensuring priority delivery in high-traffic or congested storage networks. Managed with the Emulex OneCommand management software downloadable from

HPE Software Downloads

NVMe over Fibre Channel

The SN1200E & SN1100Q 16Gb Fibre Channel Host Bus Adapters are NVMe-enabled to support emerging NVM Express (NVMe) over Fibre Channel storage networks.

- FC-NVMe support in Windows Server 2016 / 2019 with Native Multipathing (Asymmetric namespace access (ANA)) and Boot from SAN (BFS) for SN1100Q adapter
 - FC-NVMe support for ESX 7.0 U1, RHEL 8.3, RHEL 7.9, SLES 15 SP2 for SN1100Q adapter
 - Supports FC-NVMe-2 Sequence Level Error Recovery (SLER)
-

Standard Features

Active Health System

All HPE 16Gb Fibre Channel adapters support HPE ProLiant Active Health System integration. This helps administrators accurately troubleshoot and resolves problem within the server faster.

Secure Firmware download

The SN1200E delivers enhanced security via the new secure firmware update feature which protects and ensures the authenticity of device firmware.

Forward error correction (FEC)

FEC is enabled and improved at 16Gb as required by the FC Specification, automatically correcting transmission errors and improving network performance and resiliency.

Universal SAN Congestion Mitigation (USCM)

USCM support (Fabric Performance Impact Notifications, FPIN) for SN1100Q adapter in the following tools & OS distros:

- QCC CLI, ESX CLI, Windows / Linux / ESX drivers
 - USCM I/O Throttling mitigation support.
-

Link cable beaconing (LCB)

LED beaconing for ports on both ends of a physical link simplifies cable identification and management.

D-Port Diagnostics

Quickly run automated diagnostic tests in a single step, across multiple adapters, servers, and fabric components to assess connectivity. Optics and cable problems are identified and resolved.

FDMI

Quickly check connectivity to SAN devices and query the switch management server for in-depth details on connected devices.

Read Diagnostic Parameters (RDP)

Identify the source of network and media errors like cyclic redundancy check (CRC) and loss of sync (LOS) by remotely accessing diagnostic information from anywhere in the fabric.

Fabric-assigned Port Worldwide Name (FA_WWN)

Using SN1100Q & SN1200E administrators can preconfigure WWN settings at the switch port allowing Fibre Channel adapter to acquire port WWN address from the Gen 5 16Gb or Gen 6 32GFCfabric. This allows SAN administrator to configure SAN zoning without need for servers to be present.

Buffer-to-Buffer Credit Recovery (BB_CR)

The SN1100Q enhances performance and resiliency by automatically recovering buffer credits, which can be lost on long distance and lossy connections with the potential to stall I/O or degrade performance.

Standard Features

Virtual Machine ID (VM-ID)

The SN1100Q enables System/SAN administrator to monitor FC traffic from VM to LUN

Service and Support

HPE Pointnext - Service and Support

Get the most from your HPE Products. Get the expertise you need at every step of your IT journey with **HPE Pointnext Services**. We help you lower your risks and overall costs using automation and methodologies that have been tested and refined by HPE experts through thousands of deployments globally. HPE Pointnext **Advisory Services**, focus on your business outcomes and goals, partnering with you to design your transformation and build a roadmap tuned to your unique challenges. Our **Professional** and **Operational Services** can be leveraged to speed up time-to-production, boost performance and accelerate your business. HPE Pointnext specializes in flawless and on-time implementation, on-budget execution, and creative configurations that get the most out of software and hardware alike.

Recommended Services

Support for this adapter is at the level of server it is a part of. Please check the QuickSpecs of the server.

Parts and Materials

Hewlett Packard Enterprise will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product QuickSpecs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

Defective Media Retention

An option available with HPE Pointnext Complete Care and HPE Pointnext Tech Care and applies only to Disk or eligible SSD/Flash Drives replaced by HPE due to malfunction.

HPE Support Center - AI Powered and Digitally Enabled Support

Achieve faster time to resolution with access to product-specific resources and expertise through a brand-new digital and data driven customer experience. Sign-in to the all-new customer engagement platform, featuring reimagined digital case management- simplified for easy case creation and management with inline knowledge recommendations. A personalized task panel shows cases awaiting action, expiring support and more. New virtual agent - powerful AI-driven troubleshooting with seamless transition to live agent with conversation history included and the ability to verify contract, warranty, and case status. And Enhanced, intelligent search - Machine Learning tailors content easily and instantly as it's used.

Learn more <https://support.hpe.com/hpesc/public/home/signin>

Learn More

www.hpe.com/services

<https://www.hpe.com/us/en/services/operational.html>

To learn more on HPE Storage Services, please contact your Hewlett Packard Enterprise sales representative or Hewlett Packard Enterprise Authorized Channel Partner. Contact information for a representative in your area can be found at "Contact HPE" <https://www.hpe.com/us/en/contact-hpe.html>

HPE Support Services are sold by HPE and Hewlett Packard Enterprise Authorized Service Partners:

- Services for customers purchasing from HPE or an enterprise reseller are quoted using HPE order configuration tools.
-

Service and Support

- Customers purchasing from a commercial reseller can find HPE Support Services at <https://ssc.hpe.com/portal/site/ssc/>
-

Warranty

3-0-0 Three-year parts exchange warranty. Additional warranty protection can be purchased.

HPE Global Services provides a three-year, limited warranty, fully supported by a worldwide network of resellers and service providers and toll-free 24x7 hardware technical phone support for the duration of the warranty. In addition, available service offerings include a full range of HPE Pointnext operational packaged hardware and software services.

Notes: Certain restrictions and exclusions apply. Consult the [HPE Customer Support Center](#) for details.

Technical Specifications

Family Information

	P9D93A	P9D94A	Q0L13A	Q0L14A
Number of channels	Single	Dual	Single	Dual
Port Speed	16 Gbps	16 Gbps	16Gbps	16Gbps
Slot type supported	PCI Express 3.0 to Fibre Channel			
OS Supported				
Notes: Always refer to the HPE Single Point of Connectivity Knowledge for HPE Storage Products at: http://www.hpe.com/storage/spock for specific product support information and specific OS versions supported.				
Windows Server 2019/2016/ 2012 / 2012 R2 & HyperV	x64	x64	x64	x64
RHEL 8.x, 7.x, 6.x	x64	x64	x64	x64
VMware ESX/ESXi 7.0,6.7,6.5,6.0,5.5	x64	x64	x64	x64
SLES 15.x,12.x, 11.x	x64	x64	x64	x64
Servers Supported	Select HPE ProLiant & Apollo Gen10 and above platforms Notes: Refer to server Quick Specs for details regarding supported options.			
Array Platforms Supported	Refer to http://www.hpe.com/storage/spock for specific product support information			
What's Included in the Box?	16 Gbps HBA with standard bracket, one 16 Gbps SFP+, low-profile bracket, documentation	16 Gbps HBA with standard bracket, two 16 Gbps SFP+, low-profile bracket, documentation	16 Gbps HBA with standard bracket, one 16 Gbps SFP+, low-profile bracket, documentation	16 Gbps HBA with standard bracket, two 16 Gbps SFP+, low-profile bracket, documentation
Environmental - Operating Temperature	32° F to 113° F (0° C to 45° C)		32° F to 131° F (0° C to 55° C)	
Environmental - Storage Temperature	-40° F to 158° F (-40° C to 70° C)		-4° F to 158° F (-20° C to 70° C)	
Environmental - Relative Humidity - Operating	15% to 80% RH at 40° C (non-condensing)		10% to 90% RH at 40° C (non-condensing)	
Product Dimensions (W x D x H)	6.59 x 0.49 x 4.4 in (12.34x167.51x111.15mm)		6.63 x 0.63 in. (119 x 168 x 16mm)	
Media	Multi-mode Optic (SFP+)		Multi-mode Optic (SFP+)	
Connector	Short wave laser with LC type connector		Short wave laser with LC type connector	
PCIe Connector	PCIe 3.0 x8			
Auto-negotiation	16/8/4 Gbps			
Brackets	Shipped with both ½ height and full-height brackets			

Summary of Changes

Date	Version History	Action	Description of Change
10-Jan-2022	Version 21	Changed	Corrected NVMe information
07-Sep-2021	Version 20	Changed	Added UCSM and removed some of the deprecated features
04-May-2021	Version 19	Changed	Removed OBS products and added FC-NVMe OS information
03-Aug-2020	Version 18	Changed	QuickSpecs layout was updated and Branding Refresh was applied.
15-Jun-2020	Version 17	Changed	Overview and Technical Specification sections were updated
06-Apr-2020	Version 16	Changed	QuickSpecs layout was updated
07-Aug-2017	Version 15	Changed	Feature changes and Gen10 support
08-May-2017	Version 14	Changed	Changed Environmental data for SN1200E cards
17-Feb-2017	Version 13	Changed	Feature and table of specifications are cleaned up with latest information
28-Nov-2016	Version 12	Changed	Added Information on SN1200E 16Gb Single port and Dual Port adapters
07-Jun-2016	Version 11	Changed	Changes made throughout the QuickSpecs
31-Mar-2016	version 10	Changed	Changes made throughout the QuickSpecs
17-Oct-2014	Version 9	Changed	Removed the SN1000 from the name, Update the Technical Specifications section table.
09-May-2014	Version 8	Changed	Operate and Support and Basic Care were revised.
28-Mar-2014	Version 7	Changed	PCIe Connector was revised in Technical Specifications.
14-Feb-2014	Version 6	Removed	SN1000E Single Port and SN1000E Dual Port were removed.
20-Sep-2013	Version 5	Changed	Changes made to the following Sections; Overview, Models and Technical Specifications
19-Aug-2013	Version 4	Changed	QuickSpecs layout was updated
04-Dec-2012	Version 3	Changed	Changes made throughout the QuickSpecs. Note that the title has changed.
18-Jun-2012	Version 2	Changed	QuickSpecs layout was updated
13-Feb-2012	Version 1	New	New QuickSpecs

Copyright

Make the right purchase decision. Contact our presales specialists.



Chat



Email



Call



Get updates



Hewlett Packard
Enterprise

© Copyright 2022 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

c04154364 - 14202 - Worldwide - V21 - 10-January-2022