


Overview

HPE MSA 1060 Storage Array

Need a modern shared storage array which is flash-ready and affordable with what's left of a small budget? The HPE MSA 1060 Storage brings affordable flash storage down to the most price sensitive customers. Designed to meet entry-level storage requirements, the HPE MSA 1060 Storage is a good fit for budget constrained customers. With one of the lowest entry price points in the Hewlett Packard Enterprise Storage portfolio and field-proven HPE ProLiant compatibility, the HPE MSA 1060 Storage is the platform of choice for smaller IT workloads. The HPE MSA 1060 Storage features 10GBASE-T iSCSI, Fibre Channel and SAS host interface connectivity at previously unattainable entry price points. The MSA 1060 allows users to take advantage of the latest storage technologies while also providing a balance between performance and budget.



HPE MSA 1060 Storage



HPE MSA 1060 Storage-Rear View

| Item | Description  |
|------|--|
| 1.   | Power Switch   |
| 2.   | Redundant Power and Cooling Module (AC or DC)                                  |
| 3.   | Host connection ports (8/16Gb FC, 1/10Gb iSCSI or 12Gb SAS depending on model) |
| 4.   | Ethernet management port   |
| 5.   | 12Gb SAS expansion port  |
| 6.   | Controller A (Inverted)  |
| 7.   | Controller B   |

Overview

What's New

- HPE MSA Storage certification as a Backup Repository to provide seamless protection and Instant VM Recovery with Veeam Backup and Replication
- NEBS certification for HPE MSA Gen6 16Gb FC and 12Gb SAS SFF storage arrays and the MSA 2060 SFF Drive Enclosure.
- Simple, efficient, cost-effective data protection for your HPE MSA storage-hosted VMware virtual machines using HPE GreenLake's cloud-based SaaS solution, HPE GreenLake for Backup and Recovery. For further details, see "HPE GreenLake for Backup and Recovery" in the Standard Features section. No obligation, **free 90-day trial of HPE GreenLake for Backup and Recovery** is now available.

MSA 1060 Storage Models

| Description                                 | SKU    |
|---|--------|
| HPE MSA 1060 16Gb Fibre Channel SFF Storage | R0Q85B |
| HPE MSA 1060 10GBASE-T iSCSI SFF Storage    | R0Q86B |
| HPE MSA 1060 12Gb SAS SFF Storage           | R0Q87A |
| HPE MSA 1060 12Gb SAS SFF Storage           | R0Q87B |

- Notes:**
- Includes a single SFF Array Chassis, two MSA 1060 controllers, two AC power supplies, two 1.5m PDU cords (IEC C13/C14), one rack-mount kit.
  - SFPs are not required for either the iSCSI or SAS array models.
  - SFPs are required for the Fibre Channel model and must be purchased separately. SFPs are not included with the 1060 16Gb Fibre Channel model. Please refer to the "Configuration Information" section for further details.
  - All SKUs ending in "B" include the new 94% efficient power supply that meets EU Lot9 power efficiency requirements.

Standard Features

| HPE MSA 1060 Storage Array  |   |
|---|---|
| <b>Array</b>  |   |
| Access Type   | Block   |
| Form Factor   | 2U, SFF   |
| Number of controllers per array                                   | 2   |
| Number of host ports per array                                    | 4   |
| FC host connectivity  | 8/16Gb  |
| iSCSI host connectivity   | 1/10Gb  |
| SAS host connectivity   | 12Gb  |
| <b>Cache, per array</b>   |   |
| Max Read cache per array  | 8TB   |
| Data (read/write) cache + system memory per array                 | 24GB  |
| Pool Capacity   | Two Pools with 1 PB each  |
| RAID Levels supported:  | RAID 0*, 1, 5, 6, 10, MSA-DP+<br><b>Notes:</b> *Read Cache Only   |
| <b>Enclosures</b>   |   |
| Expansion Drive Enclosures  | 0-3 enclosures  |
| LFF/SFF array/enclosure mixing                                    | Supported   |
| Maximum number of drives per array enclosure                      | 24 SFF  |
| Maximum number of drives per drive enclosure                      | 24 SFF or 12 LFF  |
| Drive enclosure interface type                                    | 12Gb SAS  |
| <b>Drives</b>   |   |
| Maximum total HDDs per array                                      | 96 SFF / 24SFF + 36 LFF   |
| Maximum total SSDs per array                                      | 96 SFF / 24SFF + 36 LFF   |
| Max raw capacity per array enclosure                              | 184.32TB SFF  |
| Max raw capacity per drive enclosure                              | 184.32TB SFF / 240TB LFF  |
| Max raw capacity per array  | 737.28TB (All SFF)<br>904.32TB (SFF array + LFF drive enclosures) |
| <b>Drive Capacities</b>   |   |
| SFF SSDs  | 960GB, 1.92TB, 3.84TB, 7.68TB                                     |
| LFF SSD   | 1.92TB  |
| SFF HDDs  | 15K: 900GB<br>10K: 600GB, 1.2TB, 1.8TB, 2.4TB                     |
| LFF HDDs  | 7.2K: 6TB, 8TB, 10TB, 12TB, 14TB, 16TB, 18TB, 20TB                |
| Self-Encrypting SSDs  | SFF: 960GB, 1.92TB<br>LFF: 1.92TB                                 |
| Self-Encrypting HDDs<br><b>Notes:</b> Sold in 6 Pack bundles only | SFF: 900GB, 2.4TB<br>LFF: 12TB                                    |
| <b>Software Features</b>  |   |
| Thin Technologies   | Thin Provisioning, Space Reclamation, Thin Rebuild                |
| Tiering   | Performance Tier, Standard Tier, Archive Tier                     |
| Replication   | Snapshots (512), Volume Copy, Remote Snaps                        |
| Quality of Service  | Virtual Tier Affinity   |

Standard Features

| Additional Features   |      |
|---|------|
| Maximum number of volumes per pool                                | 512  |
| Maximum number of volumes per array                               | 1024 |
| Maximum number of snapshots (included with array)                 | 64   |
| Maximum number of snapshots (with Advanced Data Services License) | 512  |
| Maximum number of hosts   | 512  |
| Maximum number of initiators                                      | 1024 |
| Customer self-installable   | Yes  |
| Customer self-repairable  | Yes  |
| Customer self-upgradeable   | Yes  |
| Health Check analytics  | Yes  |
| Energy Star Certified   | Yes  |

All MSA 1060 models offer a common set of valuable features

Chassis

- 24 drive bay SFF 2U base storage systems
- No LFF base storage systems offered.
- 12 drive bay LFF or 24 drive bay SFF 2U expansion enclosures, depending on model
- 12Gb SAS disk expansion protocol
- Two AC power supplies with 1 black 1.5m C13/C14 PDU style jumper cord each
- New next-generation drive carriers
- Front-side bezel with support for optional bezel lock

Storage Controllers

- Dual hot-swappable active/active controllers
- 2 host ports per controller, 4 host ports per array
- 8/16Gb Fibre Channel, 1/10Gb iSCSI and 12Gb SAS protocol support
- Auto negotiation supported on Fibre Channel (down to 8Gb) and 10GBase-T iSCSI (down to 1Gb)
- New next-generation RAID offload ASIC and Processor
- 24GB system cache
- 12Gb SAS expansion ports
- Battery-free cache backup with super capacitors and compact flash

Expansion Capacity

- Maximum expansion of 3 drive enclosures (either LFF and/or SFF)
- Maximum of 96 SFF or 24SFF + 36 LFF drives
- Maximum of 737.28TB SFF (All SFF) / 904.32TB SFF + LFF Drive Enclosure mixed configuration

Storage Services

- Virtual Storage
- Up to two pools (1PB each)
- Automated tiering v2.0
- SSD read cache extension
- Thin Provisioning
- Volume Copy

### Standard Features

- Snapshot capability (64 snaps standard, 512 optional snapshot per array with Advanced Data Services License)
- Virtual Storage Disk Group can be spanned across multiple enclosures.
- Virtual Storage RAID levels supported: 1, 5, 6, 10, MSA-DP+
- New disk group type (MSA-DP+):
  - Integrated sparing
  - Fast rebuilds
  - Improved sequential performance
  - Incremental disk group expansion

### Management

- New redundant web based interface (SMU v4)
- HPE MSA Health Check
- New RESTful interface
- CLI
- Firmware Update Server - automatically receive notification of new firmware availability
- Non-disruptive on-line controller code upgrade. Requires Multi-pathing software
- Arxscan Arxview remote monitoring via HPE Complete

### Data Protection

- Remote Snapshot (Array-based asynchronous replication)
  - VMware Site Recovery Manager
  - HPE Zerto Virtual Replication
  - Optional bezel lock
- 

## Product Technology

### Storage Controllers

- The MSA 1060 FC controllers support 8/16Gb FC host connectivity.
- The MSA 1060 iSCSI controllers support 1/10GbE iSCSI host connectivity (Copper 10GBASE-T).
- The MSA 1060 SAS controllers support 12Gb SAS host connectivity.
- Dual controller active/active (dual pool) design. System can be configured as active/passive (single pool).
- Controllers contain next generation RAID offload ASIC and CPU.
- 24GB System cache
- 12Gb SAS expansion ports.

**Notes:** The MSA 1060 does not support single controller configurations. Single-controller support is provided only when a controller fails over to its partner controller.

### Modular Chassis

- New chassis design with the MSA array and drive enclosures.
- 2U rack height with 24 SFF drive bays, all 1060 array models.
- 2U rack height 12 LFF or 24 SFF drive bays, depending on 2060 drive enclosure model.
- 12G SAS Midplane
- Next generation drive modules
- New bezel lock kit for added security.

### Standard Features

#### Available Drives

The MSA 1060 Storage Systems support a wide variety of MSA 3.5-inch LFF drives (via the MSA 2060 LFF Drive Enclosure) and MSA 2.5-inch SFF drives.

- Solid-State Drives (SSDs) deliver the highest levels of performance and reliability.
  - Enterprise-class SAS hard disk drives (10K/15K RPM) offer a balance of performance, capacity, and cost while delivering enterprise grade reliability.
  - Midline SAS hard disk drives (7.2K RPM) are optimized to provide the best ratio of capacity to cost.
- 

### Optional Drive Enclosures

#### MSA 2060 LFF Drive Enclosure.

This 2U enclosure is designed to support twelve (12) HPE Storage LFF drives and accepts MSA dual-ported 12Gb SSD, Enterprise SAS HDDs, and SAS Midline HDDs. The pre-configured MSA 2060 LFF Drive enclosure has two I/O modules and supports the MSA 1060 dual Storage systems.

- The MSA 2060 LFF Drive Enclosure can be attached to the MSA 1060 SFF storage systems.
- Each MSA 2060 LFF Drive enclosure ships standard with two .5m mini-SAS HD to mini-SAS HD cables for connection to the MSA 1060 array expansion port or existing drive enclosure cascade port.
- LFF and/or SFF drive enclosures can be mixed up to the maximum of 3 total drive enclosures

#### HPE MSA 2060 SFF Drive Enclosures.

This 2U enclosure is designed to support twenty four (24) HPE Storage 2.5-inch SFF drive bays and accepts MSA dual ported 12Gb SSD, Enterprise SAS HDDs, or SAS Midline hard drives. The pre-configured MSA 2060 SFF Drive enclosure has two I/O modules and supports the MSA 1060 Storage systems.

- The MSA 2060 SFF Drive enclosure can be attached to the MSA 1060 SFF Storage systems.
  - Each MSA 2060 SFF Drive enclosure ships standard with a two .5m mini-SAS HD to mini-SAS HD cables for connection to the MSA 1060 array expansion port or existing drive enclosure cascade port.
  - LFF and/or SFF drive enclosures can be mixed up to the maximum of 3 total drive enclosures.
- 

### Scalability

- SSF configurations can scale up to 184.32TB per array enclosure, expandable to 904.32TB with the addition of a maximum of 3 MSA 2060 LFF Drive Enclosures and up to 737.28TB with the addition of a maximum of 3 MSA 2060 SFF Drive Enclosures.
  - Users may configure an MSA 1060 SFF array enclosure with MSA 2060 SFF and/or LFF Drive Enclosures.
- 

### Disk Group

A Disk Group is a collection of disks in a given redundancy mode (RAID 1, 5, 6, 10, MSA-DP+). Disk Group RAID level and size can be created based on performance and/or capacity requirements. Multiple Disk Groups can be allocated into a Storage Pool for use with the Virtual Storage features.

---

### LUNs

The MSA 1060 arrays support 512 volumes and up to 512 snapshots in a system. All of these volumes can be mapped to LUNs. Maximum LUN sizes up to 140TB. Thin Provisioning allows the user to create the LUNs independent of the physical storage.

---

### Standard Features

#### Storage Pools

Storage Pools are comprised of one or more Disk Groups. A volume's data on a given LUN can now span all disk drives in a pool. When capacity is added to a system, users will benefit from the performance of all spindles in that pool.

The MSA 1060 supports large, flexible volumes with sizes up to 128TiB and facilitates seamless capacity expansion. As pools are expanded data automatically reflows to balance capacity utilization on all drives.

#### RAID 0, 1, 5, 6, 10, MSA-DP+

The MSA 1060 features several important additional RAID levels. MSA-DP+ offers improved performance, availability, and very fast rebuild times compared to traditional parity RAID by utilizing erasure coding technology. MSA-DP+ includes distributed spare capacity (default is equal to 2x the largest drive), and does not use traditional spare drives. RAID 6 allocates two sets of parity data across drives and allows simultaneous write operations. RAID 6 can also withstand two simultaneous drive failures without downtime or data loss. RAID 10 is mirroring and striping without parity and allows large Disk Groups to be created with high performance and mirroring for fault tolerance. RAID 5 combines the block striping and parity. Because data and parity are striped across all of the disks, no single disk is a bottleneck. Striping also allows users to reconstruct data in case of a disk failure. RAID 0 (Striping) is supported for Read Cache only.

#### MSA-DP+

MSA-DP+ is a new RAID-based data protection level introduced with the 6<sup>th</sup> Generation MSA Storage Systems that:

- Maximizes flexibility
- Provides built-in spare capacity
- Optimizes performance
- Allows for very fast rebuilds, large storage pools, and simplified expansion

If a disk fails in an MSA-DP+ disk group, and the failed disk is replaced with a new disk in the same slot, the replacement disk will be added to the disk group automatically. All disks in an MSA-DP+ disk group must be the same type (enterprise SAS, for example), but can have different capacities, provided the range of difference does not exceed a factor of two. For example, mixing a 600GB disk and a 1.2TB disk is acceptable; but mixing a 6TB disk and a 16TB disk is not recommended. It is conceivable that a sizeable difference between mixed disk capacities (ratio greater than two) could prevent consuming space on disks due to insufficient distributed space required to support striping.

All disks in an MSA-DP+ disk group are used to hold user data, but not all disks will be used by each page of data. To increase fault tolerance, any available capacity on disks can be allocated as spare for reconstruction purposes. When new data is added, new disks are added, or the system recognizes that data is not distributed across disks in a balanced way, the system moves the data to maintain balance across the disk group. Spare drives are not used by MSA-DP+ disk groups since the RAID design provides built-in spare capacity that is spread across all disks in the disk group. In the case of a disk failure, data will be redistributed to many disks in the disk group, allowing for quick rebuilds and minimal disruption to I/O. The system will automatically default to a target spare capacity that is the sum of the largest two disks in the MSA-DP+ disk group, which is large enough to fully recover fault tolerance after loss of any two disks in the disk group. The actual spare capacity value can change depending on the current available spare capacity in the disk group. Spare capacity is determined by the system as disks are added to a disk group, or when disk groups are created, expanded or rebalanced.

#### Notes:

– HPE recommends not mixing disks if the ratio of the largest disk to the smallest disk is greater than two.

– For more information on MSA-DP+, refer to the [HPE MSA 1060/2060/2062 Storage Management Guide](#).



### Standard Features

---

### Configuration and Management Tools

- Management access, out-of-band, Storage Management Utility (SMU) V4, CLI.
  - Interface Types: USB 100/1000 Ethernet.
  - Protocols Supported SNMP, SMI-S, SSH, SMTP, FTP, SFTP, HTTP, HTTPS, Telnet
- 

### Web Browser Support

The MSA 1060 arrays come integrated with a new web browser (SMU v4) and CLI based software for storage and RAID management, setup, configuration, and troubleshooting. The MSA 1060 management supports Microsoft Internet Explorer, Mozilla Firefox, and Google Chrome.

---

### Hot Plug Expansion and Replacement Support

All MSA 1060 models support hot plug expansion and replacement of redundant controllers, drives, fans, power supplies, and I/O modules for simple, fast installation and maintenance. Hot add expansion of drive enclosures is also supported.

---

### HPE Server Compatibility

The MSA 1060 supports most HPE ProLiant, BladeSystems and Integrity servers including;

- HPE ProLiant DL, ML Servers
- HPE c-Class Blade Servers
- Integrity servers, IA64
- Compatibility must be confirmed at: <http://www.hpe.com/storage/spock>

**Notes:** Depends on protocol.

---

### 3<sup>rd</sup> Party Server Support

The MSA 1060 supports most multi-vendor industry standard Intel and AMD based (x86) servers. Hewlett Packard Enterprise requires the Third-Party Server to be logged and listed on the Microsoft Windows Server Catalog.

- Hewlett Packard Enterprise recommends that the Third-Party Server Vendor is an active member of TSANet. Refer to the TSANet website for details: <http://www.tsanet.com>
  - Non-HPE servers will generally be supported if the HPE storage stack is used. This includes supported HPE branded HBAs and drivers, and supported FC switches.
- 

### OS Support

Refer to the Hewlett Packard Enterprise support statements for complete current OS version support: <http://www.hpe.com/storage/spock>

- Microsoft Windows Server 2022
- Microsoft Windows Server 2019
- Microsoft Windows Server 2016
- VMware
- Red Hat Linux
- SuSE SLES Linux
- Citrix XenServer

**Notes:** depends on protocol.

---



### Standard Features

---

#### Advanced Data Services Suite

The HPE MSA Advanced Data Services Suite can be purchased as an option on the MSA 1060 Storage systems.

The optional Advanced Data Services Suite includes the following functionality:

- Performance Tiering
  - 512 Snapshots and Volume Copy
  - Remote Snap functionality
- 

#### Performance Tiering and Archive Tiering

Disk tiers are comprised of aggregating 1 or more Disk Groups of similar physical disks. The MSA 1060 supports 3 distinct tiers:

- A Performance tier with SSDs
- A Standard SAS tier with Enterprise SAS HDDs
- An Archive tier utilizing Midline SAS HDDs.

The MSA 1060 supports sub-LUN tiering and automated data movement between tiers. The MSA 1060 automated tiering engine moves data between available tiers based on the access characteristics of that data. Frequently accessed "pages" will migrate to the highest available tier delivering maximum I/O's to the application.

MSA 1060 configurations which have a mixture of both SSDs and HDDs within the same system that are configured for performance tiering will require an Advanced Data Service (ADS) Suite LTU. MSA 1060 configurations that include only SSDs or use SSD drives for Read Cache extension do not require an ADS license.

---

#### Snapshot and Volume Copy

- All MSA 1060 arrays come standard with 64 snapshots and can be expanded to 512 snapshots with the Advanced Data Services License.
  - Snapshots create up to 512 point-in-time copies of data.
  - Volume Copies create up to 128 point-in-time copies of data.
  - Volume copies become standard volumes when they are complete.
  - Recovery is instant - revert data from any previous Snapshot or Volume Copy.
  - Backup 'snapped' data to disk, virtual tape, or physical tape without a backup window.
  - If telephone support and software updates are desired for bundled software functionalities like 64 snapshots and volume copy software, a combination HW + SW support care pack must be purchased.
  - A 512 Snapshot license, included in the Advanced Data Services LTU, is available as an option on the MSA 1060.
  - Hewlett Packard Enterprise does not provide warranty assistance for software products included with our base hardware products. Support is available with either the SupportPlus or SupportPlus24 Service options. The hardware warranty component of these services is accounted for in the pricing of the SP and SP24 HPE Service options.
- 

#### Remote Snap

HPE MSA Remote Snap Software is array based functionality that provides remote replication on the HPE MSA 1060 array products. MSA Remote Snap is a form of asynchronous replication which consists of replication of block-level data from a volume on a local system to a volume on a second independent

---

### Standard Features

system. This second system may be co-located with the first system or may be located at a remote site.

- MSA Remote Snaps are used to determine the data to be replicated using the differences in snapshots on the primary volume, minimizing the amount of data to be transferred.
- MSA Remote Snap replication technology provides the ability to accomplish key data management and protection capabilities. First, because Remote Snap uses snapshots as the underlying technology can create multiple local recovery points which can be used for such tasks as to complement daily backups; second, replication provides the ability to access data in a remote site which could be used for dispersed operations; and third but definitely not least important replication allows for business continuance in the event of a failure on the primary site.
- In order to perform a replication, a snapshot of the volume to be replicated is taken, creating a point-in-time image of the data. This point-in-time image is compared to the point-in-time image taken during the previous replication and the changes are then replicated to the destination volume by copying the data represented by the snapshot via a transport medium such as TCP/IP (iSCSI) or Fibre Channel. The amount of data transferred is minimized though the use of snapshots whenever possible.
- Support of both Ethernet and Fibre Channel interconnects provides flexible options to the application environments.
- Snapshot based replication technology means only changed data will be replicated to alternate site.
- MSA Remote Snap on the MSA 1060 allows one peer connection.
- Advanced scheduler provides several options to IT administrators for business continuance
- Flexible architecture allows remote replication between MSA 1060 and MSA 2060 or MSA 2062 arrays using the virtual storage architecture and licensed for Remote Snap with the Advanced Data Services LTU.
- Snapshot based replication enables both local and remote recovery depending on the need. Snapshot replication isolates problems to a specific point in time which can be selected by the administrator. Additionally snapshot replication supports longer distance replication.
- Fast application recovery with minimal or no transaction loss.
- Creation of disaster tolerant copies of your critical business data.
- No-single-point-of-failure solution to increase the availability of your data.
- With the improved disaster recovery features of the MSA 1060, MSA 2060 and MSA 2062, you can failover to the secondary / remote volume or volume group, map the secondary volume or volume group for access, then, when the primary array has recovered, failback to the primary volume or volume group, with the option to incorporate changes made to the secondary volume or volume group back to the primary volume or volume group.
- Another improvement in Remote Snap with the MSA 1060, MSA 2060 and MSA 2062 is the ability to reverse the direction of the replication set

**Notes:** One Advanced Data Services Suite License per array is required for replication. For example, if you have two MSA arrays performing replication (from Primary system to Remote System), you will need a total of 2 licenses.

---

### HPE OneView for VMware vCenter

HPE OneView for VMware vCenter is a component within the HPE OneView plug-in for vCenter. It enables vSphere administrators to quickly obtain context-aware information and manage supported HPE storage devices like the MSA in their VMware vSphere environment directly from within vCenter. This plug-in operates independently of the core HPE OneView product and does not require a license to use.

By providing a clear relationship between VM's, datastores and storage, the VMware administrator's productivity increases, as does the ability to ensure quality of service. Roles for administrators can be defined on an individual basis, providing the ability to apply specific permissions for both view and control functions.

HPE OneView for VMware vCenter supports mixed array environments including MSA Storage, and other HPE Storage systems including Primara Storage, 3PAR Storage, Nimble Storage, and StoreOnce.

When deployed with MSA Storage, HPE OneView provides the following:

### Standard Features

- Active Management functionality for the MSA Storage:
  - Create/Expand/Delete a Datastore
  - Create a Virtual Machine from a template
- Monitors the health and status of the MSA Storage
- Displays LUN / volume connections from VMs and ESX servers to the arrays and provides the location and attributes of the MSA array within the SAN.
- Identifies what storage features are available to allow administrators to match the features available on the MSA array to their requirements.
- Provide a cluster-level view of the storage

HPE OneView for VMware vCenter is downloadable from **MSC** (My Software Center).

---

### HPE OneView for System Center

HPE OneView for Microsoft System Center provides a comprehensive integration of HPE Storage, HPE Servers, HPE Blade System and HPE Virtual Connect with Microsoft System Center. HPE OneView for System Center enables management and monitoring of HPE MSA Storage running in Microsoft environment with a single pane-of-glass view to events/alerts, capacity and health dashboards and detailed virtual infrastructure information. It provides seamless integration with Microsoft System Center Operations Manager (SCOM) enabling predefined discovery and monitoring policies, event processing rules and topology views for HPE Storage including the MSA Storage Systems.

When deployed with the MSA 1060 array, HPE OneView for System Center provides the following:

- Monitors the health, events and alerts for the MSA 1060 - virtual pools, and volumes
- Provides topology information for VMs provisioned on the MSA Storage array

HPE OneView for System Center is downloadable at no charge from **MSC** (My Software Center).

---

### vStorage API for Array Integration (VAAI)

The vStorage API for Array Integration (VAAI) is one of the storage application programming interface (API) sets in vSphere. VAAI is an API storage partners can leverage to enhance performance of virtual machine (VM) management operations by delegating these operations to the storage array. With hardware offload, ESX/ESXi hosts perform certain operations faster and consume less server CPU and memory resources, and also storage port and storage fabric bandwidth. VAAI includes high performance and scalable VM data path primitives.

Storage Hardware Primitives for VAAI

- Full Copy or Hardware Assisted Move
  - Block Zeroing or Hardware Assisted Zeroing
  - Hardware Assisted Locking or Atomic Test and Set (ATS)
  - UNMAP reclaims space that is no longer on a thinly provisioned VMFS volume
- 

### LDAP Support

LDAP (Lightweight Directory Access Protocol) is an industry standard application protocol for accessing and maintaining distributed directory information services over an IP network. LDAP provides the ability to authenticate MSA users with a central directory.

- Domain or Directory Credentials are not stored on the MSA for authentication - avoids a security issue
  - Once user groups are configured on all MSAs in your organization, users can be authenticated on any MSA through the Active Directory
  - Uses an LDAP implementation to authenticate users with a Windows Active Directory
  - The MSA CLI and SMU will allow the configuration of new LDAP users groups into the MSA security
-

### Standard Features

- scheme (manage vs monitor users, interface restrictions Web/CLI/FTP)
- Ability to authenticate Local or LDAP users

### I/O Workload Functionality

A beneficial user interface element called "I/O Workload" is included in the MSA web browser (SMU v4). The MSA array controllers keep track of a substantial amount of data pertaining to the I/O dynamics at a logical page level (4MB chunks). From this data, it is possible to provide some visibility to what percent of I/O's are being processed by what percent of the overall array's capacity across a 7 day timeline. While some workloads have "transient" data access patterns, many workloads have steady access patterns on small portions of the array's capacity. This produces "hot" pages in the array which remain hot a large amount of the array's uptime. Users would see substantial benefits if these pages could be served from the fastest media in the array (ideally SSDs).

As has been described in the MSA's tiering functionality, the MSA array's tiering engine will work to position the hottest pages on the fastest media at any given time.

The new I/O Workload graph will show a line labeled Capacity and a line plot for each selected workload percentage (100%, 80%, or Other% value). Below are two examples of user scenarios where the I/O Workload Graph might be useful and how to utilize the data the graph provides.

- New User or SSD Installation.
- Once the MSA array is installed and has had workloads running against it for a week's time, the I/O Workload data will give a representation of what capacity is servicing; 100% of I/O and 80% of I/O. Users may select a custom % value if desired. In a new installation or in an installation with no SSD tier installed, the 80% line is a reasonable starting point for an SSD tier. Based on SSD RAID settings, customers can then calculate a good starting point with regard to SSD tier sizing based on that week's workload. While not a hard fast rule, it is a good starting point. These values should also be compared to the Best Practices "rule of thumb" which suggest that 5-15% of the array's capacity should be SSDs for tiered solutions.
- Users with existing SSD tiering or read caching installed and running.
- For arrays running with SSDs installed (tiered or read cache), the I/O Workload graph will have a dotted line which shows the installed SSD capacity. The I/O Workload graphs can be checked periodically to see where the 80% I/O line is with regard to the SSD capacity line. While there are no hard and fast rules which indicate good/bad situations, users can use the graph with other system performance tools to better understand specific dynamics of their installation and the normal dynamics of a system in the day-to-day activities for a specific environment.


Interpreting the I/O Workload graphs allow users to strike a balance between the SSD costs versus performance benefits. For example, some customers may be willing to have a couple of days where peak usage is far above the SSD capacity line as it may be acceptable to have slower performance as the system uses HDDs for a larger percentage of the workload I/O. This may be perfectly acceptable for systems sized to optimize \$/TB due to budget constraints. Other users may want to optimize the system such that a sizeable percentage of daily I/O have the opportunity to reside on SSD media (sized to 80% or 90%). When combined with other performance monitoring tools, the new I/O Workload function gives users some representation as to how the workloads and the MSA are working together in a user's real-world environment.

### Protect your data with HPE MSA Storage and Veeam Backup & Replication

Together, HPE and Veeam help you safeguard your data to ensure it's always on, always protected and that your enterprise can rapidly and easily recover should a situation arise - from human error to a malicious attack. And now, HPE MSA Storage is certified as a Backup Repository to provide seamless protection and Instant VM Recovery. Veeam Backup & Replication provides a single management console to orchestrate the protection of virtual servers, physical machines and cloud-based workloads. Due to the extraordinary ratio of cost to capacity and performance offered by HPE MSA Storage, Veeam Backup & Replication with HPE MSA Storage makes the perfect solution to modernize your backup strategy and

### Standard Features

protect your data from disaster.



Key features of Veeam Backup and Replication:

- Image-level VM backups: Create application-consistent backups with advanced application-aware processing.
- Higher data availability with efficient movement of backup copies offsite for disaster recovery
- Unify management of protection of physical and cloud environments
- Scale-out Backup Repository: Create a single virtual pool of backup storage to which backups can be assigned, offering the freedom to easily extend backup storage capacity.
- SureBackup: Automatically test and verify every backup and every VM for recoverability.
- Image-based VM replication with WAN acceleration: Get backups off site up to 50x faster than non-accelerated traffic and save bandwidth for offsite for disaster recovery (DR).
- Direct Storage Access: Perform vSphere backups faster and with reduced impact by backing up via Direct SAN Access and Direct NFS Access.
- Instant VM Recovery: Restore access to a failed VM in less than two minutes while the full restore is executed in parallel.
- Native tape support: Store entire VM backups or individual files on HPE StoreEver with direct restore from tape.
- SureReplica: Automatically test and verify every VM replica for recoverability.

For more details on Veeam Backup & Replication see the [Veeam Backup & Replication](#) web pages.

### HPE Zerto

HPE MSA Storage users can leverage Zerto Virtual Replication to replicate applications and data from one MSA array to another MSA array. Popular use cases include departmental MSA storage replicated to enterprise storage, enterprise storage replicated into MSA array, or protect MSA workloads into the cloud.

Zerto operates on the hypervisor level and includes orchestration and automation built-in to enable faster recovery of workloads (RTO in minutes) at much lower Recovery Point Objective (RPO of seconds) available through other data protection tools like backup. Zerto is also a workload mobility tool and allow IT to confidently move workloads and data across heterogeneous storage or cloud.

### Standard Features

Ordering, configuring and installing Zerto is simple. Zerto is licensed by number of Virtual Machines that are being protected or moved. For mobility use cases, order the appropriate number of migration licenses needed. For replication use cases, order the appropriate quantity of Zerto Virtual Replication licenses using a combination of the tiered licenses plus the corresponding maintenance part numbers. The license is independent of source and target array size, type or capacity being replicated. See the HPE Complete/Zerto QuickSpec for a complete list of part numbers. A corresponding MSA Advanced Data Services LTU is not required for data replication when using Zerto Virtual Replication. An MSA Advanced Data Services LTU would be required if deploying MSA array-based replication.

Zerto installs as a virtual machine under VMware or Hyper-V or in the Cloud as a VM in AWS and Azure in minutes. Zerto does not install any components in the guest operating system and does not depend on any specific configuration of the storage or use MSA array or VMware snapshots to replicate and recover applications.

Review the [HPE Zerto quickspec](#) for more information.

---

### HPE Complete - Arxscan

Arxscan is an HPE Complete Partner delivering innovative software that drives value through unique enterprise data center monitoring and reporting. Arxscan provides infrastructure monitoring for Storage, Network, Servers and Applications. Arxscan is fully supported on the HPE MSA 1060, 2060 and 2062 storage arrays, and is available for purchase directly from Hewlett Packard Enterprise. Arxscan's intuitive dashboard delivers an unprecedented view of how organizations store, distribute and protect their data, providing relevant views around device quality and performance metrics. Benefits include:

- Remote delivery from any location to any location worldwide.
- Supports all HPE arrays, storage OEM product lines, SAN switch and server OS platforms without agents.
- Quickly installed in under two hours in SMB, midrange or enterprise customer environments.
- Presents views that are business operations and infrastructure/system operations centric.
- Creates global collaborative touch points for all users of local and remote data center resources.
- One Stop Shop - ability to purchase complete solutions from HPE that include both HPE products and best-in-class third party branded products, all on a single HPE purchase order.

For more information please refer to [HPE Complete](#) on [HPE.com](#)

---

### HPE GreenLake for Backup and Recovery

HPE GreenLake for Backup and Recovery is a hybrid cloud data protection service delivered through the Data Services Cloud Console (DSCC) application on the HPE GreenLake edge-to-cloud platform. It protects on-premises VMware infrastructure and AWS cloud resources through a unified management console. HPE GreenLake for Backup and Recovery uses prebuilt and customizable global protection policies to enable automated data protection and create consistent immutable recovery points.

HPE GreenLake for Backup and Recovery provides access to hybrid cloud data protection for virtual machines located on HPE MSA storage through on-premises rapid data recovery and cost-effective long-term retention in the cloud. HPE GreenLake for Backup and Recovery makes protection of your on-premises and cloud-native assets easy with global policy-based automation, secure encryption, and backup data immutability. HPE GreenLake for Backup and Recovery utilizes efficient data protection technologies with built-in data reduction enabling predictable consumption-based billing for cost savings across the hybrid cloud. To learn more about the features and benefits of using this SaaS-based data protection solution, go to [HPE GreenLake for Backup and Recovery](#) on [HPE.com](#).

### Standard Features

To experience the simplicity and efficiency of HPE GreenLake for Backup and Recovery with your HPE MSA Storage, HPE GreenLake now offers a 90-day free trial with no further obligations. See how easy it is to protect your on-premises HPE VM volumes in just a few simple steps. Visit "[\*\*Try HPE GreenLake for Backup and Recovery - Free\*\*](#)" to request your free 90-trial of HPE GreenLake for Backup and Recovery.

---

### HPE MSA Health Check Tool

MSA Health Check is a cloud-based tool that provides users insight into the general health of their MSA array. The tool uses a powerful rules-based analytics engine which can predict failures before they happen. The MSA Health Check tool performs a full sweep of analytics and checking thousands of data points from sensors inside the MSA array. The analytics engine will pick up common failure signatures and check against MSA best practices producing a simple, easy to digest PDF report with status and suggested courses of action to correct anything found in the scan. The tool is free of charge to HPE MSA customers. The MSA Health Check tool is supported across all current MSA 1060/2060/2062 arrays as well as the prior three generations of arrays (MSA P2000 G3, MSA 1040/2040/2042 and MSA 1050/2050/2052).

The tool is available immediately at: [\*\*http://www.hpe.com/storage/MSAHealthCheck\*\*](http://www.hpe.com/storage/MSAHealthCheck).

For more information on how to use HPE MSA Health Check, please review the [\*\*HPE MSA Health Check User Guide\*\*](#).

---

### ENERGY STAR Certification

The HPE MSA 1060 SAN Storage systems are ENERGY STAR certified. ENERGY STAR certified products are energy efficient which result in cost savings via reduced energy consumption and regulatory rebates. Please refer to the US EPA website for details on ENERGY STAR certification criteria and process. MSA 1060 ENERGY STAR Certification is listed on the EPA website.

---

### NEBS Certification

When used in conjunction with specific Storage SFF SAS drives and the MSA 2060 764W -48VDC Hot Plug Power Supply Kit (R0Q90A), the HPE MSA 1060 16Gb FC SFF Storage (R0Q85A/R0Q85B) and MSA 1060 12Gb SAS SFF Storage (R0Q87A/R0Q87B) arrays are certified compliant with GR-63-Core (Issue 5) and GR-1089-Core (Issue 7) NEBS criteria. NEBS Certified DC-Power Storage systems are designed for network equipment providers (NEPs) and communication service providers. All NEBS compliant MSA 2060 Storage systems support configurations with up to 3 compliant 2060 SFF Drive Enclosures (R0Q40A/R0Q40B) for a maximum of 240 SFF HDDs or SSDs

---



### Service and Support

#### Warranty

- MSA Storage Systems carry a 3 year limited warranty, parts only exchange, normal business hours, next business day response.
  - MSA Enterprise SAS (15K and 10K RPM) SFF HDDs carry a 3 year limited warranty, parts only exchange, normal business hours, next business day response.
  - MSA Midline SAS (7.2K RPM) LFF HDDs carry a 1 year limited warranty, parts only exchange, normal business hours, next business day response.
  - MSA SSDs carry a 3 year limited warranty, parts only exchange, normal business hours, next business day response. MSA 1060 SSD warranty includes unconditional replacement in case of drive failure, media wear-out, or both.
  - The MSA 1060 has been designed with customer self-repairable parts to minimize repair time and provide greater flexibility in performing defective parts replacement. Please refer to Hewlett Packard Enterprise limited warranty Statement and parts replacement instructions for further details.
- 

#### HPE Service and Support

**Get the most from your HPE Products.** Get the expertise you need at every step of your IT journey with **HPE Services**. We help you lower your risks and overall costs using automation and methodologies that have been tested and refined by HPE experts through thousands of deployments globally. HPE **Advisory Services**, focus on your business outcomes and goals, partnering with you to design your transformation and build a roadmap tuned to your unique challenges. Our **Professional** and **Operational Services** can be leveraged to speed up time-to-production, boost performance and accelerate your business. HPE Services specializes in flawless and on-time implementation, on-budget execution, and creative configurations that get the most out of software and hardware alike.

#### Consume IT on your terms

**HPE GreenLake** brings the cloud experience directly to your apps and data wherever they are-the edge, colocations, or your data center. It delivers cloud services for on-premises IT infrastructure specifically tailored to your most demanding workloads. With a pay-per-use, scalable, point-and-click self-service experience that is managed for you, HPE GreenLake accelerates digital transformation in a distributed, edge-to-cloud world..

- Get Faster time to market
- Save on TCO, align costs to business
- Scale quickly, meet unpredictable demand
- Simplify IT operations across your data centers and clouds

#### Managed services to run your IT operations

**HPE Managed Services** provides services that monitor, operate, and optimize your infrastructure and applications, delivered consistently and globally to give you unified control and let you focus on innovation.

---

#### Free up resources with Operational Services from HPE

HPE delivers services for IT by using proven best practices as well as automation and methodologies that have been tested and refined by HPE experts and artificial intelligence through thousands of deployments globally. Choose from the recommended services for customers purchasing from Hewlett Packard Enterprise or an authorized reseller. Services are quoted using Hewlett Packard Enterprise order configuration tools.

#### Recommended Services

##### HPE Tech Care Service

HPE Tech Care is the new operational service experience for HPE products. Tech Care goes beyond traditional support by providing access to product specific experts, an AI driven digital experience, and general technical guidance to not only reduce risk but constantly search for ways to do things better. HPE

---

### Service and Support

Tech Care has been reimagined from the ground up to support a customer-centric, AI driven, and digitally enabled customer experience to move your business forward. HPE Tech Care is available in three response levels. Basic, which provides 9x5 business hour availability and a 2 hour response time.

Essential which provides a 15 minute response time 24x7 for most enterprise level customers, and Critical which includes a 6 hour repair commitment where available and outage management response for severity 1 incidents.

For more information, visit the [\*\*HPE Tech Care Services\*\*](#) website.

#### **HPE Complete Care**

HPE Complete Care is a modular, edge-to-cloud IT environment service that provides a holistic approach to optimizing your entire IT environment and achieving agreed upon IT outcomes and business goals through a personalized and customer-centric experience. All delivered by an assigned team of HPE Services experts. HPE Complete Care provides:

- A complete coverage approach -- edge to cloud
- An assigned HPE team
- Modular and fully personalized engagement
- Enhanced Incident Management experience with priority access
- Digitally enabled and AI driven customer experience

For more information, visit the [\*\*HPE Complete Care Service\*\*](#) website.

---

### Related Services

#### **HPE Hardware Installation**

Provides for the basic hardware installation of HPE branded servers, HPE storage including the MSA 1060 devices and networking options to assist you in bringing your new hardware into operation in a timely and professional manner.

#### **HPE Installation and Startup Service**

Provides for the installation and startup of HPE technology including BladeSystems, c-Class enclosure, HPE ProLiant c-Class and Integrity server blades, storage blades, SAN switch blades, HPE Virtual Connect modules (Ethernet and Fibre Channel), Ethernet network interconnects, and InfiniBand, as well as the installation of one supported operating system type (Windows® or Linux).

#### **HPE Factory Express for Servers and Storage**

HPE Factory Express offers configuration, customization, integration and deployment services for HPE servers and storage products. Customers can choose how their factory solutions are built, tested, integrated, shipped and deployed.

Factory Express offers service packages for simple configuration, racking, installation, complex configuration and design services as well as individual factory services, such as image loading, asset tagging, and custom packaging. HPE products supported through Factory Express include a wide array of servers and storage: HPE Integrity, HPE ProLiant, HPE Apollo, HPE ProLiant Server Blades, HPE BladeSystem, as well as the HPE MSA Storage, HPE Primera Storage, HPE 3PAR Storage, HPE XP Storage, rackable tape libraries and configurable network switches.

#### **HPE Education Services**

Keep your IT staff trained making sure they have the right skills to deliver on your business outcomes. Book a class today and learn how to get the most from your technology investment.

<http://www.hpe.com/ww/learn>

---

### Service and Support

#### **HPE Support Center**

The HPE Support Center is a personalized online support portal with access to information, tools and experts to support HPE business products. Submit support cases online, chat with Hewlett Packard Enterprise experts, access support resources or collaborate with peers.

Learn more at the **[HPE Support Center](http://www.hpe.com/services)**.

HPE Insight Remote Support and HPE Support Center are available at no additional cost with a HPE warranty, HPE Support Service or HPE contractual support agreement.

For more information: **<http://www.hpe.com/services>**

---

#### **Parts and Materials**

Hewlett Packard Enterprise will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product QuickSpecs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

The defective media retention service feature option applies only to Disk or eligible SSD/Flash Drives replaced by Hewlett Packard Enterprise due to malfunction.

---

Configuration Information

Step 1: MSA 1060 Base Configurations

Pre-Configured Systems

| Description                                 | SKU    |
|---|--------|
| <b>MSA 1060 Storage Systems</b>             |        |
| HPE MSA 1060 16Gb Fibre Channel SFF Storage | R0Q85B |
| HPE MSA 1060 10GBASE-T iSCSI SFF Storage    | R0Q86B |
| HPE MSA 1060 12Gb SAS SFF Storage           | R0Q87A |
| HPE MSA 1060 12Gb SAS SFF Storage           | R0Q87B |

Notes:

- Includes a SFF Array Chassis, two MSA 1060 controllers, two AC power supplies, two 1.5m PDU cords (IEC C13/C14), one rack-mount kit.
- SFPs are not included with the Fibre Channel array model, and are not required for the iSCSI or SAS array model.
- There are no SAN models with the MSA 1060 Storage Systems.
- All SKUs ending in "B" include the new 94% efficient power supply that meets EU Lot9 power efficiency requirements.
- HPE MSA 1060 models R0Q85A/R0Q85B and R0Q87A/R0Q87B are compliant with NEBS criteria for GR-63-Core (Issue 5) and GR-1089-Core (Issue 7). See "Step 3" and "Step 4" for NEBS supported drive and power supply options or refer to "NEBS Certification" section for further details.

Step 2: Select Your SFP+ Module

|   |        |
|---|--------|
| HPE MSA 16Gb Short Wave Fibre Channel SFP+ 4-pack Transceiver | C8R24B |
|---|--------|

Notes:

- Th MSA SFP (C8R24B) is for use with the MSA 1060 Fibre Channel Storage system (R0Q85A) only.
- MSA 1060 Fibre Channel Storage systems do not ship with SFPs - they must be purchased separately
- One SFP 4 pack transceiver is required for the 1060 Fibre Channel model.
- MSA 1060 SAS and iSCSI Storage systems do not require SFP modules.

Step 3: Select your Drives

- MSA Gen 6 HDDs and SSDs are for use with MSA Gen 6 Storage Systems only.
- MSA Gen 6 HDDs and SSDs are not compatible with prior generation MSA Storage Systems
- Prior Generation of MSA HDDs and SSDs are not compatible with MSA Gen 6 Storage Systems.
- MSA 1060 array models only accept SFF HDD and SSD options - to use LFF drives with your array configuration, you must add a 2060 LFF Drive Enclosure (R0Q39A or R0Q39B).
- Customers can mix SSD, Enterprise SAS, and SAS Midline (MDL) drives in the same array enclosure or drive enclosure
- Configurations which have a mixture of both SSDs and HDDs within the same system that are being configured for performance tiering (excluding SSD Read Cache) will require the Advanced Data Service (ADS) Suite LTU.
- Configurations with all SSDs or with a SSD Read Cache extension do not require an ADS license on the MSA1060 array.

SFF HDD 6-Pack Bundles

Select MSA SFF HDD options are available to purchase in bundles that include 6 drives. Purchasing MSA drives in bundles typically provides a lower purchase price than purchasing them individually. Check with your HPE sales representative or channel partner for further details.

|   |        |
|---|--------|
| HPE MSA 5.4TB SAS 12G Enterprise 15K SFF (2.5in) M2 3yr Wty 6-pack HDD Bundle | R0Q64A |
|---|--------|

## Configuration Information

**Notes:** Contains 6 x MSA 900GB 12G SAS 15K SFF Enterprise HDDs (R0Q53A)

**Description****SKU**

HPE MSA 7.2TB SAS 12G Enterprise 10K SFF (2.5in) M2 3yr Wty 6-pack HDD Bundle

R0Q65A

**Notes:** Contains 6 x MSA 1.2TB 12G SAS 10K SFF Enterprise HDDs (R0Q55A).

Certified for use in NEBS certified MSA Gen6 configurations.

HPE MSA 10.8TB SAS 12G Enterprise 10K SFF (2.5in) M2 3yr Wty 6-pack HDD Bundle

R0Q66A

**Notes:** Contains 6 x MSA 1.8TB 12G SAS 10K SFF Enterprise HDDs (R0Q56A).

Certified for use in NEBS certified MSA Gen6 configurations.

HPE MSA 14.4TB SAS 12G Enterprise 10K SFF (2.5in) M2 3yr Wty 6-pack HDD Bundle

R0Q67A

**Notes:** Contains 6 x MSA 2.4TB 12G SAS 10K SFF Enterprise HDDs (R0Q57A).

Certified for use in NEBS certified MSA Gen6 configurations.

**LFF HDD 6-Pack Bundles**

Select MSA LFF HDD options are available to purchase in bundles that include 6 drives. Purchasing MSA drives in bundles typically provides a lower purchase price than purchasing them individually. Check with your HPE sales representative or channel partner for further details.

**Notes:** LFF drives can only be added to a MSA1060 array configuration using the 2060 LFF Drive Enclosure (R0Q39A or R0Q39B).

HPE MSA 48TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty 6-pack HDD Bundle

R0Q69A

**Notes:** Contains 6 x MSA 8TB 12G SAS 7.2K LFF Midline HDDs (R0Q59A)

HPE MSA 60TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty 6-pack HDD Bundle

R0Q70A

**Notes:** Contains 6 x MSA 10TB 12G SAS 7.2K LFF Midline HDDs (R0Q60A)

HPE MSA 72TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty 6-pack HDD Bundle

R0Q71A

**Notes:** Contains 6 x MSA 12TB 12G SAS 7.2K LFF Midline HDDs (R0Q61A)

HPE MSA 84TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty 6-pack HDD Bundle

R0Q72A

**Notes:** Contains 6 x MSA 14TB 12G SAS 7.2K LFF Midline HDDs (R0Q62A)

HPE MSA 96TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty 6-pack HDD Bundle

R3U73A

**Notes:** Contains 6 x MSA 16TB 12G SAS 7.2K LFF Midline HDDs (R3U72A)

HPE MSA 108TB SAS 12G Midline 7.2K LFF M2 1-year Warranty 6-pack HDD Bundle

R7L71A

**Notes:** Contains 6 x MSA 18TB 12G SAS 7.2K LFF Midline HDDs (R7L70A)

HPE MSA 120TB SAS 12G Midline 7.2K LFF M2 1-year Warranty 6-pack HDD Bundle

S0F33A

**Notes:** Contains 6 x MSA 20TB 12G SAS 7.2K LFF Midline HDDs (S0F32A)

**Self-Encrypting HDD 6-Pack Bundles**

Select MSA Self-Encrypting (SED) HDD options are available to purchase in bundles that include 6 drives. Purchasing MSA drives

in bundles typically provides a lower purchase price than purchasing them individually. Check with your HPE sales representative or channel partner for further details.

**Notes:** LFF drives can only be added to a MSA1060 array configuration using the 2060 LFF Drive Enclosure (R0Q39A or R0Q39B).

HPE MSA 5.4TB SAS 12G Enterprise 15K SFF (2.5in) M2 3yr Wty FE 6-pack TAA-compliant HDD Bundle

R0R44A

**Notes:** Contains 6 x MSA 900GB 12G SAS 15K SFF FE HDDs

**Description****SKU**

HPE MSA 14.4TB SAS 12G Enterprise 10K SFF (2.5in) M2 3yr Wty FE 6-pack TAA-compliant HDD Bundle

R0R47A

Configuration Information

Notes: Contains 6 x MSA 2.4TB 12G SAS 10K SFF FE HDDs

HPE MSA 72TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty FE 6-pack TAA-compliant HDD Bundle R0R50A

Notes: Contains 6 x MSA 12TB 12G SAS 7.2K LFF FE HDDs

Notes:

- All drives within the MSA 1060 array must be self-encrypted drives to enable the encryption feature.
- SEDs can be used in a non-SED configuration.
- All MSA SEDs are FIPS 140-2 validated self-encrypting drives
- All MSA SEDS have been certified by the U.S. National Institute of Standards and Technology (NIST) and Canadian Communications Security Establishment (CSE) as meeting the Level 2 security requirements for cryptographic modules as defined in the FIPS 140-2 Publication.
- All SED drives are TAA compliant. However, this does not apply to the TAA compliance for the array or the entire configuration. If array TAA compliance is required, please select the appropriate MSA Gen5 TAA-compliant array model. MSA Gen6 array models are not TAA compliant.

SFF HDDs

|   |        |
|---|--------|
| HPE MSA 900GB SAS 12G Enterprise 15K SFF (2.5in) M2 3yr Wty HDD | R0Q53A |
| HPE MSA 600GB SAS 12G Enterprise 10K SFF (2.5in) M2 3yr Wty HDD | R0Q54A |
| HPE MSA 1.2TB SAS 12G Enterprise 10K SFF (2.5in) M2 3yr Wty HDD | R0Q55A |
| HPE MSA 1.8TB SAS 12G Enterprise 10K SFF (2.5in) M2 3yr Wty HDD | R0Q56A |
| HPE MSA 2.4TB SAS 12G Enterprise 10K SFF (2.5in) M2 3yr Wty HDD | R0Q57A |

Notes: MSA 1.2TB, 1.8TB, and 2.4TB 10K SFF HDD options are certified for use in NEBS certified MSA Gen6 configurations.

LFF HDDs

Notes: LFF drives can only be added to a MSA1060 array configuration using the 2060 LFF Drive Enclosure (R0Q39A or R0Q39B).

|  |        |
|--|--------|
| HPE MSA 6TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty HDD  | R0Q58A |
| HPE MSA 8TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty HDD  | R0Q59A |
| HPE MSA 10TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty HDD | R0Q60A |
| HPE MSA 12TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty HDD | R0Q61A |
| HPE MSA 14TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty HDD | R0Q62A |
| HPE MSA 16TB SAS 12G Midline 7.2K LFF (3.5in) M2 1yr Wty HDD | R3U72A |
| HPE MSA 18TB SAS 12G Midline 7.2K LFF M2 1-year Warranty HDD | R7L70A |
| HPE MSA 20TB SAS 12G Midline 7.2K LFF M2 1-year Warranty HDD | S0F32A |

SFF SSDs

|  |        |
|--|--------|
| HPE MSA 960GB SAS 12G Read Intensive SFF (2.5in) M2 3yr Wty SSD          | R0Q46A |
| HPE MSA 1.92TB SAS 12G Read Intensive SFF (2.5in) M2 3yr Wty SSD         | R0Q47A |
| HPE MSA 3.84TB SAS 12G Read Intensive SFF (2.5in) M2 3yr Wty SSD         | R3R30A |
| HPE MSA 7.68TB SAS 12G Read Intensive SFF (2.5in) M2 3-year Warranty SSD | S0F31A |

Notes: MSA 960GB, 1.92TB, and 3.84TB SSD options are certified for use in NEBS certified MSA Gen6 configurations.

LFF SSDs

Notes: LFF drives can only be added to a MSA1060 array configuration using the 2060 LFF Drive Enclosure (R0Q39A or R0Q39B).

| Description | SKU |
|-------------|-----|
|-------------|-----|

Configuration Information

HPE MSA 1.92TB SAS 12G Read Intensive LFF (3.5in) M2 3yr Wty SSD R0Q49A

Self-Encrypting Drives (SED)

Notes: LFF drives can only be added to a MSA1060 array configuration using the 2060 LFF Drive Enclosure (R0Q39A).

HPE MSA 960GB SAS 12G Read Intensive SFF (2.5in) M2 3yr Wty FIPS Encrypted TAA-compliant SSD R0R52A

HPE MSA 1.92TB SAS 12G Read Intensive SFF (2.5in) M2 3yr Wty FIPS Encrypted TAA-compliant SSD R0R53A

HPE MSA 1.92TB SAS 12G Read Intensive LFF (3.5in) M2 3yr Wty FIPS Encrypted TAA-compliant SSD R0R55A

Notes:

- All drives within the MSA 1060 array must be self-encrypted drives to enable the encryption feature.
- SEDs can be used in a non-SED configuration.
- All MSA SEDs are FIPS 140-2 validated self-encrypting drives
- All MSA SEDS have been certified by the U.S. National Institute of Standards and Technology (NIST) and Canadian Communications Security Establishment (CSE) as meeting the Level 2 security requirements for cryptographic modules as defined in the FIPS 140-2 Publication.
- All SED drives are TAA compliant. However, this does not apply to the TAA compliance for the array or the entire configuration. If array TAA compliance is required, please select the appropriate MSA Gen5 TAA-compliant array model. MSA Gen6 array models are not TAA compliant.

Step 4: Options

Drive Enclosures

HPE MSA 2060 SAS 12G 2U 12-disk LFF Drive Enclosure R0Q39B

HPE MSA 2060 SAS 12G 2U 24-disk SFF Drive Enclosure R0Q40B

Notes:

- Each drive enclosure includes a single rack-mount kit and two 0.5m MiniSAS HD to MiniSAS HD cables.
- Add up to 3 additional drive enclosures.
- MSA 2060 SFF or LFF Drive Enclosures can be connected to the MSA 1060 SFF Storage systems.
- All SKUs ending in "B" include the new 94% efficient power supply that meets EU Lot9 power efficiency requirements.
- The HPE MSA 2060 SFF Drive Enclosure, R0Q40A/R0Q40B, is compliant with NEBS criteria for GR-63-Core (Issue 5) and GR-1089-Core (Issue 7). See "Step 3" and "Step 4" for NEBS supported drive and power supply options or refer to "NEBS Certification" section for further details.

Drive Enclosure Cables

HPE External 1.0m (3ft) Mini-SAS HD 4x to Mini-SAS HD 4x Cable 716195-B21

HPE External 2.0m (6ft) Mini-SAS HD 4x to Mini-SAS HD 4x Cable 716197-B21

Notes: When connecting a MSA 1060 controller to a drive enclosure if a longer cable is needed.

Security Option

HPE Bezel Lock Kit 875519-B21

Notes: Each array and drive enclosure chassis includes a bezel. This option includes a lock for securing the bezel.

DC Power Option

Description SKU



Configuration Information

HPE MSA 2060 764W -48VDC Hot Plug Power Supply Kit R0Q90A

Notes:

- All MSA 1060 array enclosures and drive enclosures come standard with two AC power supplies.
- If DC power is desired, then two DC power supplies must be selected on the array enclosure and all drive enclosures.
- DC Power Supplies can be ordered with factory integration or with field integration. With factory integrated orders, the AC power supplies will not be shipped.
- One (1) 48VDC 2.3M power cord is included with each R0Q90A kit.
- Required for use in NEBS compliant MSA Gen6 configuration.

Power Cords

|   |        |
|---|--------|
| HPE C13 - C14 WW 250V 10Amp 2.0m Jumper Cord            | A0K02A |
| HPE C13-NEMA 6-15P 10A/250V 3.6m Black Power Cord       | A0N33A |
| HPE C13 - Nema 5-15P US/CA 110V 10Amp 1.83m Power Cord  | AF556A |
| HPE C13 - GB-1002 CN 250V 10Amp 1.83m Power Cord        | AF557A |
| HPE C13 - IRAM -2073 AR 250V 10A 2.5m Power Cord        | AF558A |
| HPE C13 - KSC- 8305 KR 250V 10Amp 1.83m Power Cord      | AF560A |
| HPE C13 - CNS-690 TW 110V 13Amp 1.83m Power Cord        | AF561A |
| HPE C13 - IS-1293 IN 240V 6Amp LV 2.0m Power Cord       | AF562A |
| HPE C13 - SI-32 IL 250V 10Amp 1.83m Power Cord          | AF564A |
| HPE C13 - SEV 1011 CH 250V 10Amp 1.83m Power Cord       | AF565A |
| HPE C13 - DK-2.5A DK 250V 10Amp 1.83m Power Cord        | AF566A |
| HPE C13 - SABS-164 ZA 250V 10Amp 2.5m Power Cord        | AF567A |
| HPE C13 - CEE-VII EU 250V 10Amp 1.83m Power Cord        | AF568A |
| HPE C13 - AS3112-3 AU 250V 10Amp 2.5m Power Cord        | AF569A |
| HPE C13 - BS-1363A UK/HK/SG 250V 10Amp 1.83m Power Cord | AF570A |
| HPE C13 - JIS C8303 JP 100V 12Amp 2.0m Power Cord       | AF572A |
| HPE C13 - C14 WW 250V 10Amp Flint Gray 2.0m Jumper Cord | AF573A |
| HPE C13 - NBR-14136 BR 250V 10Amp 1.83m Power Cord      | AF591A |
| HPE C13-C14 IN 250V 10Amp 2m Black Jumper Cord          | R1C65A |

Notes:

- Two PDU cables, 1.5m black C13/C14, ship standard with all AC-powered enclosures
- The above power cord options may be used by customers that desire to plug their base array and/or drive enclosures into a wall outlet or require a different length PDU Jumper Cord.

Step 5: Choose cables for host connection

Fibre Channel Infrastructure

PremierFLeXOM4 type cables

| Description   | SKU    |
|---|--------|
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 1m Cable  | QK732A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 2m Cable  | QK733A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 5m Cable  | QK734A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 15m Cable | QK735A |
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 30m Cable | QK736A |

Configuration Information

|   |        |
|---|--------|
| HPE Premier Flex LC/LC Multi-mode OM4 2 Fiber 50m Cable | QK737A |
|---|--------|

OM3 Fibre FC to LC cables

|  |        |
|--|--------|
| HPE LC to LC Multi-mode OM3 2-Fiber 0.5m 1-Pack Fiber Optic Cable  | AJ833A |
| HPE LC to LC Multi-mode OM3 2-Fiber 1.0m 1-Pack Fiber Optic Cable  | AJ834A |
| HPE LC to LC Multi-mode OM3 2-Fiber 2.0m 1-Pack Fiber Optic Cable  | AJ835A |
| HPE LC to LC Multi-mode OM3 2-Fiber 5.0m 1-Pack Fiber Optic Cable  | AJ836A |
| HPE LC to LC Multi-mode OM3 2-Fiber 15.0m 1-Pack Fiber Optic Cable | AJ837A |
| HPE LC to LC Multi-mode OM3 2-Fiber 30.0m 1-Pack Fiber Optic Cable | AJ838A |
| HPE LC to LC Multi-mode OM3 2-Fiber 50.0m 1-Pack Fiber Optic Cable | AJ839A |

10GBase-T Infrastructure

Ethernet Cables

Notes: CAT 6 cables or above are required.

SAS Infrastructure

Min-SAS HD to Mini-SAS HD Fanout Cables

|  |        |
|--|--------|
| HPE Mini SAS High Density to Dual 2-lane Mini SAS High Density External Fanout 1 Meter Cable | K2Q99A |
| HPE Mini SAS High Density to Dual 2-lane Mini SAS High Density External Fanout 2 Meter Cable | K2R00A |
| HPE Mini SAS High Density to Dual 2-lane Mini SAS High Density External Fanout 4 Meter Cable | K2R01A |

Notes:

- These cables are used to connect HPE ProLiant DL and ML servers to MSA 1060 SAS Storage system.
- These cables are used for direct connect of more than two hosts.
- These cables are not used for connecting the MSA 1060 to a drive enclosure.

Mini SAS HD to Mini SAS Cables

|   |            |
|---|------------|
| HPE 1.0m External Mini SAS High Density to Mini SAS Cable | 716189-B21 |
| HPE 2.0m External Mini SAS High Density to Mini SAS Cable | 716191-B21 |
| HPE 4.0m External Mini SAS High Density to Mini SAS Cable | 716193-B21 |

Notes:

- These cables are used to connect the c-Class 6Gb BladeSystem SAS switch to MSA 1060 SAS Storage system.
- These are not used for connecting the MSA 1060 to a drive enclosure.

Mini SAS HD to Mini SAS HD Cables

| Description   | SKU        |
|---|------------|
| HPE External 1.0m (3ft) Mini-SAS HD 4x to Mini-SAS HD 4x Cable  | 716195-B21 |
| HPE External 2.0m (6ft) Mini-SAS HD 4x to Mini-SAS HD 4x Cable  | 716197-B21 |
| HPE External 4.0m (13ft) Mini-SAS HD 4x to Mini-SAS HD 4x Cable | 716199-B21 |

Notes:

- Each kit includes a single cable that can support up to 4 lanes.
- These cables are used to connect the DL and ML ProLiant 12Gb SAS Servers to MSA 1060 SAS Storage system.
- Limited to two redundantly connected hosts.
- Fanout cables are highly recommended.

Configuration Information

- The 1.0m and 2.0m Mini-SAS HD to Mini-SAS HD cables can also be used for connecting a MSA 1060 SAS controller to a SFF or LFF drive enclosure.

Step 6: Software

|   |          |
|---|----------|
| HPE MSA 2060 Advanced Data Services LTU   | R2C33A   |
| HPE MSA 2060 Advanced Data Services E-LTU | R2C33AAE |

Notes:

- The Advanced Data Services Suite includes a Performance Tiering LTU, 512 Snapshot Software LTU, and the Remote Snap Software LTU.
- Configurations which have a mixture of both SSDs and HDDs within the same system that are being configured for performance tiering (excluding SSD Read Cache) will require the Advanced Data Service (ADS) Suite LTU.
- Configurations with all SSDs or with a SSD Read Cache extension do not require an ADS license on the MSA1060 array.
- Visit [HPE Complete](#) on [HPE.com](#) for information on Zerto Virtual Replication and Arxscan Arxview software that is supported on the MSA 1060/2060/2062 Storage.

## Technical Specifications

| <b>MSA 1060</b>   |   |
|---|---|
| <b>Power Requirements</b>                                     |   |
| Input Power Requirements (typical-running I/O) SFF/LFF arrays | 120VAC 3.07A, 293-361 W<br>220VAC 1.58A, 289-352W   |
| Max Input Power   | 100-240 VAC, 50/60 Hz., 4.38-2.17A; 48-60 VDC<br>10.4A/8.3A   |
| Heat Dissipation  | 1766 BTU/hr   |
| <b>Temperature and Humidity Ranges</b>                        |   |
| Operating Temperature   | ASHRAE A3 5°C to 40°C, -12°C DP & 8 to 24°C DP<br>(Derate maximum allowable dry-bulb temperature<br>1°C/175m above<br>900m) |
| Shipping Temperature  | -40°F to 158°F (-40°C to 70°C)  |
| Operating Humidity  | Up to 85% RH  |
| Non-Operating Humidity  | Up to 90% RH @ 30°C   |
| <b>Physical</b>   |   |
| Height  | 3.5 in (8.9 cm)   |
| Depth (Back of chassis ear to controller latch)               | 20.0 in (50.8 cm)   |
| Depth (Front of chassis ear to back of cable bend)            | 26.4 in (66.9 cm)   |
| Width (Chassis only)  | 17.5 in (44.5 cm)   |
| Width (Chassis with bezel ear caps)                           | 19.0 in (48.3 cm)   |
| <b>Weight LFF Enclosure</b>                                   |   |
| Chassis empty   | 11 lb (5 kg)  |
| Controller enclosure(fully populated with FRUs and disks)     | 71 lb (32 kg)   |
| Expansion enclosure (fully populated with FRUs and disks)     | 62 lb (28 kg)   |
| <b>Weight SFF Enclosure</b>                                   |   |
| Chassis empty   | 11 lb (5 kg)  |
| Expansion enclosure (fully populated with FRUs and disks)     | 66 lb (30 kg)   |
| Controller enclosure(fully populated with FRUs and disks)     | 55 lb (25 kg)   |
| <b>Acoustic Ratings</b>                                       |   |
| Sound Power   | A weighted sound power LWAd - 8.3 B   |
| Sound Pressure  | A weighted sound pressure LpAm - 74dBA  |
| <b>Shock and Vibration</b>                                    |   |
| Shock, Operational  | 5G, 11 ms   |
| Shock, Non-Operational  | 15G, 10ms   |
| Vibration, Operational  | 5-500Hz, 0.18 Grms  |
| Vibration, Non-Operational                                    | x-axis (5-300Hz) 0.8 Grms<br>z-axis (5-300Hz) 1.2 Grms  |

### Technical Specifications

| Power Supply Details                         |  |          |          |
|--|--|----------|----------|
| 2U Flex 580W PSU 80+ Gold                    |  |          |          |
| Input Voltage Range (V rms)                  | 100-240  |          |          |
| Frequency Range (Hz)                         | 50-60  |          |          |
| Nominal Input Voltage                        | 115  | 208      | 230      |
| Maximum Output Wattage Rating (W)            | 584  | 584      | 584      |
| Nominal Input Current (Arms)                 | 5.7  | 3.2      | 2.8      |
| Maximum Input Wattage Rating (W)             | 652  | 645      | 644      |
| Maximum Rated VA (VA)                        | 653  | 661      | 650      |
| Efficiency (%/100)                           | 0.896  | 0.905    | 0.907    |
| Power Factor                                 | 0.999  | 0.976    | 0.991    |
| Leakage Current (mA)                         | <0.8   |          |          |
| Maximum Inrush Current (A peak)              | 45   |          |          |
| Maximum Inrush Current Duration (ms)         | 40   |          |          |
| Maximum British Thermal Unit Rating (BTU-hr) | 2224.233   | 2201.382 | 2196.286 |
| 2U Flex 580W PSU 80+ Platinum                |  |          |          |
| Input Voltage Range (V rms)                  | 100-240  |          |          |
| Frequency Range (Hz)                         | 50-60  |          |          |
| Nominal Input Voltage                        | 115  | 208      | 230      |
| Maximum Output Wattage Rating (W)            | 584  | 584      | 584      |
| Nominal Input Current (Arms)                 | 5.56   | 3.06     | 2.77     |
| Maximum Input Wattage Rating (W)             | 639.4  | 635.5    | 630      |
| Maximum Rated VA (VA)                        | 640.3  | 636.1    | 625.2    |
| Efficiency (%/100)                           | 0.913  | 0.919    | 0.935    |
| Power Factor                                 | 0.999  | 0.999    | 0.999    |
| Leakage Current (mA)                         | <0.8   |          |          |
| Maximum Inrush Current (A peak)              | 45   |          |          |
| Maximum Inrush Current Duration (ms)         | 40   |          |          |
| Maximum British Thermal Unit Rating (BTU-hr) | 2180.4   | 2167.0   | 2148.3   |
| MSA 1060 Regulatory Information              |  |          |          |
| <b>Safety</b>                                | <ul style="list-style-type: none"> <li>UL/CSA 62368-1 (USA/Canada)</li> <li>EN 62368-1 (European Union)</li> <li>IEC 60950-1 (International)</li> </ul>  |          |          |
| <b>Power</b>                                 | <ul style="list-style-type: none"> <li>EU Regulation 2019/424 (Lot 9)</li> </ul>   |          |          |
| <b>Electromagnetic Compatibility</b>         | <ul style="list-style-type: none"> <li>VCCI Class A (Japan)</li> <li>FCC Class A (USA)</li> <li>ICES-003 Class A (Canada)</li> <li>EN55032 : (European Union Class A); CISPR 32 (International Class A)</li> <li>EN61000-3-2 : (Harmonics) (European Union)</li> <li>EN61000-3-3 : (Flicker) (European Union)</li> <li>EN 55024 (European Union, Immunity, Class A); CISPR 24 (International Immunity, Class A)</li> <li>AS/NZS CISPR 32, Class A (Australia, New Zealand)</li> <li>CNS 13438 Taiwan, Class A (Taiwan)</li> <li>KN32 Class A (Emissions Class A); KN35 (Immunity) (S Korea)</li> </ul> |          |          |
| <b>RoHS and WEEE</b>                         | <ul style="list-style-type: none"> <li>RoHS-6/6</li> <li>China RoHS</li> <li>WEEE</li> </ul>   |          |          |
| <b>Country Approvals</b>                     | United States, Australia/New Zealand, Canada, European Union, Japan, South Korea, Taiwan   |          |          |

MSA 1060 Benchmark Performance Results

The performance figures provided here are for reference as many variables exist between array configurations, workloads, drive types, disk group setup parameters and host system setup. Hewlett Packard Enterprise has traditionally published a set of end-to-end MSA performance specifications that are fed into HPE Sizer tools which are based on conservative real-world configurations. For consistency, the MSA performance numbers have been documented in both Benchmark and End-to-End Performance tables. Complete End-to-End Performance results will be provided for the MSA 1060 in a subsequent publication. These numbers are subject to change without notice

| HPE MSA 1060 Benchmark Performance Results  |                          |
|---|--------------------------|
| Benchmark Performance Results <sup>1</sup>  | HPE MSA 1060 (with SSDs) |
| IOPS  |                          |
| Random Reads <sup>2</sup>   | 154,000                  |
| Random Writes <sup>3</sup>  | 60,000                   |
| Sequential <sup>4</sup>   |                          |
| Segmented Sequential Reads <sup>5</sup>   | 6.6 GB/s                 |
| Segmented Sequential Writes <sup>6</sup>  | 6.5 GB/s                 |
| Notes:  |                          |
| – <sup>1</sup> Performance results were generated using internal HPE test tools. Number and type of applications, drive type and number of drives, operating system used, and the number of hosts will affect overall performance. This table is provided strictly as a test-lab comparison.  |                          |
| – <sup>2</sup> Dual controller configuration, four SSDs, RAID 10, two SSDs per disk group; one disk groups per pool, two volumes per pool, block size: 8k, 16Gb FC direct connect to array.   |                          |
| – <sup>3</sup> Dual controller configuration, four SSDs, RAID 10, two SSDs per disk group; one disk groups per pool, two volumes per pool, block size: 8k, 16Gb FC direct connect to array.   |                          |
| – <sup>4</sup> Sequential performance numbers were generated using segmented sequential workloads. For segmented sequential workloads with a queue depth greater than 1, each sequential stream is targeted to operate on a separate LBA range. Other types of sequential workloads that target specific LBA ranges may achieve higher results. |                          |
| – <sup>5</sup> Dual controller configuration, 96 10k RPM HDDs, RAID: 10, nine drives per disk group, 13 disk groups per pool, two volumes per pool, block size: 256k, 16Gb FC direct connect to array.  |                          |
| – <sup>6</sup> Dual controller configuration, 90 10k RPM HDDs, RAID 5, nine drives per disk group, 13 disk groups per pool, two volumes per pool, block size 256k, 16Gb FC direct connect to array.   |                          |

| MSA 1060 End-to-End Performance Figures                       |                      |         |                          |         |                       |         |
|---|----------------------|---------|--------------------------|---------|-----------------------|---------|
| Storage Model   | MSA 1060 FC          |         | MSA 1060 iSCSI           |         | MSA 1060 SAS          |         |
| Host Protocol   | 16Gb FC <sup>2</sup> |         | 10GbE iSCSI <sup>2</sup> |         | 12Gb SAS <sup>2</sup> |         |
| Drive Technology  | HDD                  | SSD     | HDD                      | SSD     | HDD                   | SSD     |
| MSA 1060 RAID1 / RAID 10 Performance Results <sup>3,4,5</sup> |                      |         |                          |         |                       |         |
| Random Reads IOPs   | 18,900               | 142,700 | 19,000                   | 115,900 | 19,000                | 137,400 |
| Random Writes IOPs  | 18,100               | 56,000  | 18,100                   | 48,500  | 18,100                | 55,700  |
| Random Mix 60/40 IOPs   | 17,900               | 83,900  | 18,000                   | 70,700  | 17,900                | 81,500  |
| Sequential Reads MB/s <sup>1</sup>                            | 6,100                | 6,100   | 2,900                    | 4,400   | 7,000                 | 7,000   |
| Sequential Writes MB/s <sup>1</sup>                           | 4,700                | 5,400   | 2,900                    | 3,800   | 4,600                 | 5,200   |
| MSA 1060 RAID 5 Performance Results <sup>5,6</sup>            |                      |         |                          |         |                       |         |



## Technical Specifications

|                                     |        |         |        |         |        |         |
|-------------------------------------|--------|---------|--------|---------|--------|---------|
| Random Reads IOPs                   | 17,700 | 132,500 | 17,700 | 109,300 | 17,700 | 128,400 |
| Random Writes IOPs                  | 9,100  | 31,300  | 9,300  | 28,400  | 9,300  | 30,800  |
| Random Mix 60/40 IOPs <sup>1</sup>  | 11,200 | 55,000  | 11,200 | 48,700  | 11,200 | 54,000  |
| Sequential Reads MB/s <sup>1</sup>  | 6,100  | 6,100   | 4,400  | 4,400   | 7,000  | 7,000   |
| Sequential Writes MB/s <sup>1</sup> | 5,600  | 6,000   | 3,900  | 3,800   | 5,400  | 5,700   |

MSA 1060 RAID 6 Performance Results<sup>7,8</sup>

|                                     |        |         |        |         |       |         |
|-------------------------------------|--------|---------|--------|---------|-------|---------|
| Random Reads IOPs                   | 16,500 | 131,500 | 16,400 | 109,000 | 8,900 | 127,200 |
| Random Writes IOPs                  | 6,000  | 28,000  | 6,000  | 25,800  | 5,600 | 27,800  |
| Random Mix 60/40 IOPs <sup>1</sup>  | 7,700  | 51,000  | 7,700  | 45,400  | 6,600 | 50,200  |
| Sequential Reads MB/s <sup>1</sup>  | 6,100  | 6,100   | 4,400  | 3,000   | 6,900 | 7,100   |
| Sequential Writes MB/s <sup>1</sup> | 5,600  | 6,000   | 3,800  | 2,900   | 5,400 | 5,600   |

MSA 1060 MSA-DP+ Performance Results<sup>9,10</sup>

|                                     |        |         |        |         |        |         |
|-------------------------------------|--------|---------|--------|---------|--------|---------|
| Random Reads IOPs                   | 18,800 | 129,300 | 18,700 | 107,700 | 18,700 | 124,900 |
| Random Writes IOPs                  | 7,000  | 27,900  | 7,000  | 25,800  | 7,000  | 27,600  |
| Random Mix 60/40 IOPs <sup>1</sup>  | 9,200  | 50,700  | 9,300  | 45,200  | 9,200  | 49,900  |
| Sequential Reads MB/s <sup>1</sup>  | 6,100  | 6,100   | 2,900  | 4,400   | 7,000  | 7,100   |
| Sequential Writes MB/s <sup>1</sup> | 5,500  | 6,000   | 2,900  | 3,800   | 5,200  | 5,600   |

## Notes:

– Number and type of applications, drive type and number of drives, operating system used, and the number of hosts will affect overall performance. This table is provided strictly as a test-lab comparison. These numbers reflect a full array configuration with the maximum number of front-end ports and controllers. The test results shown for the HPE MSA 1060 are designed to give a conservative reference point for comparisons.

– All performance numbers were captured using dual controller configurations.

– All performance numbers were captured using 2 volumes per pool.

o <sup>1</sup>Sequential tests (MB/s) are based on 256K block sizes and random tests (IOPS) are based on 8K block sizes. For sequential workloads with a queue depth greater than 1, each sequential stream is targeted to operate on a separate LBA range. Other types of sequential workloads that target specific LBA ranges may achieve higher results. Results cannot be expected with a single host.

o <sup>2</sup>Fibre Channel results were measured using 16 Gb FC Host Bus Adapters. SAS results were measured using 12 Gb SAS Host

o <sup>3</sup>Bus Adapters. 10 GbE iSCSI results were measured using 10GbE iSCSI Host Bus Adapters. Hosts were directly attached to the HPE MSA 1060 array.

o <sup>4</sup>RAID 10 Solid State Drive random results: (4) SSDs, 2 SSDs per disk group, 1 disk group per pool.

o <sup>5</sup>RAID 10 Hard Disk Drive results: (96) 10K HDD, 10 drives per disk group, 12 disk groups per pool.

o <sup>6</sup>RAID 5 Solid State Drive random results: (6) SSDs, 3 SSDs per disk group, 1 disk group per pool.

o <sup>7</sup>RAID 5 Hard Disk Drive results: (90) 10K HDD, 9 drives per disk group, 13 disk groups per pool.

o <sup>8</sup>RAID 6 Solid State Drive random results: (8) SSDs, 4 SSDs per disk group, 1 disk group per pool.

o <sup>9</sup>RAID 6 Hard Disk Drive results: (80) 10K HDD, 10 drives per disk group, 12 disk groups per pool.

o <sup>10</sup>MSA-DP+ Solid State Drive results: (24) SSDs, 12 SSDs per disk group, 1 disk group per pool.



Technical Specifications

o <sup>11</sup>MSA-DP+ Hard Disk Drive results: (96) 10K HDD, 30 drives per disk group, 15 disk groups per pool.

Environment-friendly Products and Approach End-of-life Management and Recycling

Hewlett Packard Enterprise offers end-of-life product return, trade-in, and recycling programs, in many geographic areas, for our products. Products returned to Hewlett Packard Enterprise will be recycled, recovered or disposed of in a responsible manner.



The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard Enterprise web site. These instructions may be used by recyclers and other WEEE treatment facilities as well as Hewlett Packard Enterprise OEM customers who integrate and re-sell Hewlett Packard Enterprise equipment.

### Summary of Changes

| Date        | Version History | Action  | Description of Change  |
|-------------|-----------------|---------|--|
| 19-Jun-2023 | Version 12      | Changed | Overview, Standard Features and Configuration Information sections were updated.<br>Added NEBS certification details, support for Veeam, and other general updates.  |
| 06-Feb-2023 | Version 11      | Changed | Overview and Standard Features sections were updated<br>HPE GreenLake for Backup and Recovery content added.   |
| 05-Dec-2022 | Version 10      | Changed | Overview, Standard Features and Configuration Information sections were updated.<br>Added 20TB HDD, 20TB HDD six-pack, and 7.68TB SSD drive options  |
| 06-Sep-2022 | Version 9       | Changed | Overview, Standard Features, Configuration information and Technical Specifications sections were updated<br>Added MSA 1060 Storage Array and MSA 2060 Drive Enclosure SKU additions for Lot9 2023 compliance. |
| 13-Jun-2022 | Version 8       | Changed | Overview, Standard Features, service and Support and Configuration Information sections were updated.  |
| 04-Oct-2021 | Version 7       | Changed | Service and Support section was updated  |
| 02-Aug-2021 | Version 6       | Changed | Service and Support section was updated  |
| 06-Jul-2021 | Version 5       | Changed | Update to What's New section, 48VDC power cord, and other updates.   |
| 06-Apr-2021 | Version 4       | Changed | Added 18TB HDD option, updated OS support, updated temperature and humidity specifications   |
| 18-Jan-2021 | Version 3       | Changed | Added power supply details, system certifications, and other textual updates.  |
| 16-Nov-2020 | Version 2       | Changed | Added shock, vibe, and acoustic specifications. Updated SFP messaging. Updated HDD and SSD options   |
| 08-Sep-2020 | Version 1       | New     | New QuickSpecs.  |

Copyright

Make the right purchase decision. Contact our presales specialists.



© Copyright 2023 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Intel® and Xeon® are registered trademarks of Intel Corporation in the U.S. and other countries.  
Microsoft®, Windows®, and Windows Server® are U.S. registered trademarks of the Microsoft group of companies.

For hard drives, 1GB = 1 billion bytes. Actual formatted capacity is less

a00094628enw - 16614 - Worldwide - V12 - 19-June-2023