



## Archer TX20U Plus

# AX1800 Dual Antennas High Gain Wireless USB Adapter

- **Lightning-Fast WiFi 6** – Stream flawless video with 1800 Mbps wireless speeds (1201 Mbps on 5 GHz + 574 Mbps on 2.4 GHz)<sup>†</sup>
- **Flexible Dual Band** – Ensure your PC has the best connection with 5 GHz and 2.4 GHz bands
- **Dual High-Gain Antennas** – Connect from farther away with high-quality signals and transmissions
- **MU-MIMO** – Maintain high download and upload speeds even when other devices are eating up your bandwidth<sup>△</sup>
- **OFDMA** – Reduce your latency for impeccable conferencing and gameplay on crowded networks<sup>△</sup>
- **SuperSpeed USB 3.0** – Up to 10× faster transfer speeds than USB 2.0
- **Refined Security** – Protect your personal data with the latest WPA3 encryption
- 

- **CARACTERÍSTICAS DE HARDWARE**

<b>LED</b>	Status
<b>Dimensiones</b>	84 × 156.3 × 19.2 mm (3.3 × 6.2 × 0.76 in)
<b>Antena</b>	2× High-Gain Dual-Band Antennas

- **CARACTERÍSTICAS INALÁMBRICAS**

<b>Estándares Inalámbricos</b>	IEEE 802.11a/b/g/n/ac/ax
	5 GHz:
	11ax: Up to 1201 Mbps(dynamic)
	11ac: Up to 867 Mbps(dynamic)
	11n: Up to 300 Mbps(dynamic)
	11a: Up to 54 Mbps(dynamic)
<b>Tasa de Señal</b>	2.4 GHz:
	11ax: Up to 574 Mbps(dynamic)
	11n: Up to 400 Mbps(dynamic)
	11g: Up to 54 Mbps(dynamic)
	11b: Up to 11 Mbps(dynamic)
	5 GHz:
	11ax HE80 MCS0: -90 dBm
	11ax HE80 MCS11: -59 dBm
<b>Sensibilidad de Recepción</b>	11a 54Mbps: -77 dBm
	11ac VHT80 MCS0: -92dBm
	11ac VHT80 MCS9: -64dBm
	2.4 GHz:

## CARACTERÍSTICAS INALÁMBRICAS

	11ax HE40 MCS0: -94 dBm
	11ax HE40 MCS11: -66 dBm
	11g 54Mbps: -79 dBm
	11n HT40 MCS9: -74dBm
<b>Potencia de Transmision</b>	5 GHz: 19dBm(FCC) /16dBm(CE) (EIRP) 2.4 GHz : 19dBm(FCC) / 14.5dBm(CE) (EIRP)
<b>Modos Inalámbricos</b>	Infrastructure mode
<b>Seguridad Inalámbrica</b>	WEP, WPA/WPA2/WPA3, WPA-PSK/WPA2-PSK
	<b>Otros</b>
<b>Certificacion</b>	FCC, CE, RoHS
<b>Contenidos del Paquete</b>	AX1800 Dual Antennas High Gain Wireless USB Adapter Archer TX20U Plus Quick Installation Guide 1-meter USB 3.0 Cable
<b>Requisitos del Sistema</b>	Supported operating systems include Windows 10, 11
<b>Ambiente</b>	Operating Temperature: 0°C~40°C (32°F ~104°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing