



## TP-Link Omada EAP613 punto de acceso inalámbrico 1775 Mbit/s Blanco Energía sobre Ethernet (PoE)

Marca : TP-Link

Familia de productos: Omada Código del producto: EAP613

Nombre del producto :  
EAP613

TP-Link Omada EAP613. 2.4 GHz, 5 GHz, Rango máximo de transferencia de datos: 1775 Mbit/s.  
Algoritmos de seguridad: HTTPS, SNMP, SNMPv2, SNMPv3, WPA, WPA2, WPA3. Ethernet LAN, velocidad de transferencia de datos: 100,1000 Mbit/s. Energía sobre Ethernet (PoE). Color del producto: Blanco.  
Consumo de energía (máx.): 10.6 W



Features		Power	
2.4 GHz *	✓	Power over Ethernet (PoE) *	✓
5 GHz *	✓	Power over Ethernet (PoE) type supported	Passive PoE
6 GHz *	✗	DC voltage range	12 V
Maximum data transfer rate *	1775 Mbit/s	Input current	1 A
Maximum data transfer rate (2.4 GHz)	574 Mbit/s	Power consumption (typical)	9.6 W
Maximum data transfer rate (5 GHz)	1201 Mbit/s	Power consumption (max)	10.6 W
Ethernet LAN data rates	100,1000 Mbit/s	<b>Design</b>	
Frequency band	2.4 - 5 GHz	Placement *	Ceiling, Wall
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Product colour *	White
Automatic channel selection	✓	Reset button	✓
Automatic channel scanning	✓	LED indicators	✓
MIMO	✓	<b>Antenna</b>	
MIMO type	Multi User MIMO	Antenna type *	Internal
Spread spectrum method	OFDMA	Antennas quantity	4
Wi-Fi Multimedia (WMM)/(WME)	✓	Antenna gain level (max)	5 dBi
VLAN support	✓	<b>Performance</b>	
Rate limiting	✓	Compatible operating systems	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux
Wireless isolation	✓	<b>Certificates</b>	
Band steering	✓	Certification	CE, FCC, RoHS
Airtime Fairness (ATF)	✓	<b>Weight &amp; dimensions</b>	
BeamForming	✓	Width	160 mm

Features		Weight & dimensions	
Transmitting power (CE)	<20 dBm(2.4 GHz, EIRP); <23 dBm(5 GHz band1/2, EIRP); <25 dBm (5 GHz band3)	Depth	160 mm
Transmitting power (FCC)	<25 dBm (2.4 GHz); <25 dBm (5 GHz)	Height	33.6 mm
Security		Packaging content	
Security algorithms *	HTTPS, SNMP, SNMPv2, SNMPv3, WPA, WPA2, WPA3	Quantity per pack	1 pc(s)
Number of SSID supported	16	Mounting kit	✓
Management features		Operational conditions	
Web-based management	✓	Operating relative humidity (H-H)	0 - 40%
Management platform	Omada	Operating temperature (T-T)	10 - 90 °C
Ports & interfaces		Storage temperature (T-T)	-40 - 70 °C
Ethernet LAN (RJ-45) ports *	1	Storage relative humidity (H-H)	5 - 90%
DC-in jack	✓		