

- Plataforma
 - Intel®Raptor Lake-U U300 SoC
 - Intel®Raptor Lake-U Core™ i3-1315U SoC
 - Intel®Raptor Lake-U Core™ i5-1335U SoC
 - Intel®Raptor Lake-U Core™ i5-1345U SoC (vPRO supported)
 - Intel®Raptor Lake-U Core™ i7-1355U SoC
 - Intel®Raptor Lake-U Core™ i7-1365U SoC (vPRO supported)
- Expansión de Slot
 - 4 x COM Ports
 - └ COM1 & 2: RS232/422/485 supported
 - └ COM3 & 4: RS232 supported
- Memoria
 - Support 2 x SO-DIMM DDR4 3200MHz, up to 64GB
- Almacenamiento
 - 1 x M.2 2280 PCIe GEN4 x 4 NVME SSD
 - Support 1 x 2.5" SATA HDD / SSD (optional)
- Audio
 - 1 x Combo Jack
- Conexión redes
 - 2 x 2.5 Gbps LAN (LAN 1: i226 LM & i226V vPRO co-layout)
- USB
 - 3 x USB 3.2 Gen 2x1 (Front I/O)
 - 1 x USB 4 Gen 2x2 Type C (Front I/O)
 - 1 x USB 2.0 (Internal Header 2x5)
- Salida de Video
 - 2 x HDMI™ (HDMI™ 1: w/ CEC function; Power on/off only)
 - 1 x DP1.4 HBR3
 - 1 x Type C (alt DP)
- Inalámbrico
 - 1 x M.2 2230 WLAN 802.11ax
- Alimentación
 - 19V/4.74A, 90W
- Montaje VESA
 - Supports 75mm / 100mm
- Dimensions (mm)
 - 148 x 120 x 53.9 (mm)
- OS Soportado
 - Windows® 10 IOT
 - Windows® 11 Home & Pro
 - Linux
- Accesorio
 - ADAPTER / SCREW / VESA MOUNT / QUICK GUIDE
- Observación
 - 1 x TPM IC Onboard (Optional)

*The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.