TP-Link TL-SG1006PP dispositivo de redes No administrado Gigabit Ethernet (10/100/1000) Energía sobre Ethernet (PoE) Gris

Marca : TP-Link

Código del producto: TL-SG1006PP

Nombre del producto : TL-SG1006PP

TP-Link TL-SG1006PP. Tipo de interruptor: No administrado. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 6. Tabla de direcciones MAC: 4000 entradas, Capacidad de conmutación: 12 Gbit/s. Estándares de red: IEEE 802.1p, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. Voltaje de entrada DC: 53.5 V. Energía sobre Ethernet (PoE). Montaje en rack

Management features	
Switch type *	Unmanaged
Quality of Service (QoS) support	✔
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity *	6
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)
Network	
Networking standards *	IEEE 802.1p, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x
10G support *	✘
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6
Flow control support	✔
Auto MDI/MDI-X	✔
Ethernet LAN data rates	10,100,1000 Mbit/s
Auto-negotiation	✔
MAC address auto-learning supported	✔
MAC address auto-aging supported	✔
Data transmission	
Switching capacity *	12 Gbit/s
Forwarding rate	8.928 Mpps
MAC address table *	4000 entries
Store-and-forward	✔
Security	
IGMP snooping	✔
Design	
Rack mounting *	✔
Stackable *	✔
Product colour	Grey

Design	
LED indicators	✔
Performance	
Fanless	✔
Power	
Power source *	DC/PoE
Power supply included *	✔
DC input voltage	53.5 V
Input current	1.31 A
Power consumption (typical)	4.75 W
Power consumption (max)	71.46 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✔
Power over Ethernet (PoE) ports quantity	4
Total Power over Ethernet (PoE) budget	64 W
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Heat dissipation	16.2 BTU/h
Weight & dimensions	
Width	158 mm
Depth	101 mm
Height	25 mm
Packaging content	
Quick start guide	✔
Packaging data	
Package type	Box
Certificates	
Certification	FCC, CE, RoHS