

Especificaciones

Eaton 9PX6KG2



Eaton 9PX Gen 2 UPS, 6000 VA, 5400 W,
Input: Hardwired or 10ft. L6-30P, Outputs:
Hardwired, (2) L6-30R, (2) L6-20R, 3U
Rack/tower, VRLA battery, Gigabit Network
card included



General specifications

PRODUCT NAME	Eaton 9PX UPS
CATALOG NUMBER	9PX6KG2
UPC	786689860066
PRODUCT LENGTH/DEPTH	26.93 in
PRODUCT HEIGHT	5.12 in
PRODUCT WIDTH	17.32 in
PRODUCT WEIGHT	98.33 lb
COMPLIANCES	CISPR22 Class A / FCC part 15 Class A FCC Part 15 CE Marked
CERTIFICATIONS	NOM cULus Listed IEC 62040-2:2006 Cat C2 ENERGY STAR certified ICC-ES AC156 OSHPD Seismic certified

Especificaciones del producto

Recursos

SPECIAL FEATURES	Gigabit Network Card (NETWORK-M3) included
TOPOLOGY	Online/Double-conversion
FORM FACTOR	Rack/tower
RACK SIZE	3U
COLOR	Black/silver
VA RATING	6000 VA
WATTAGE	5400 W
RACK MOUNTING KIT	Yes

PACKAGE CONTENTS

- 6000VA 5400W 9PX G2 Online Double-Conversion UPS
- NETWORK-M3 Gigabit network card
- USB cable
- RS-232 cable
- Cable gland for hardwire connection
- Rack-mounting hardware
- Tower support stands
- Quick Start Guide

SURGE PROTECTION	Yes
INTERNAL BYPASS	Yes
INPUT CONNECTION	L6-30P and hardwire input supported
INPUT CORD LENGTH	10 ft
INPUT NOMINAL VOLTAGE	208V default (200/208/220/230/240V)
INPUT FREQUENCY RANGE	60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz
INPUT POWER FACTOR	>0.99 typical
RECEPTACLE	(2) L6-20R, (2) L6-30R, Hardwired
NUMBER OF OUTPUTS L6-20R	2
NUMBER OF OUTPUTS L6-30R	2
OUTPUT WAVEFORM	True sine wave
VOLTAGE	208 V
OUTPUT NOMINAL VOLTAGE	208V default (200/208/220/230/240V)

RUNTIME GRAPH	\$row.attributeValue.cdata
BATTERY MANAGEMENT	ABM+ technology uses battery replacement analytics to predict when you should replace UPS batteries based on real-life usage and conditions.
BATTERY REPLACEMENT	Hot-swappable internal batteries and extended battery modules (EBMs). Replacement battery part # EBP-1805 (qty 1 per UPS)
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	Add up to 12 EBMs, part # 9PXEBM180RTG2
STANDARD FACTORY WARRANTY	• 3-YEAR FACTORY WARRANTY • - 3 years • - Parts, electronics and batteries coverage • - Standard ground shipping • - Technical support
EXTENDED SERVICE PLANS	• ADVANCED DEPOT EXCHANGE • - 5-year depot repair: 9SW5Y-6000UC • - Expedited parts coverage for 5 years • - Parts, electronics and UPS batteries coverage • - Next business day shipping • - Technical support • • 5 YEAR ON-SITE PLAN: WFLN75XX-6009UC • - On-site parts and labor coverage for 5 years • - Parts, electronics and UPS batteries coverage • - 24x7 on-site labor coverage, next day response

- - Next-day shipping
- - Technical support

RUNTIME AT HALF LOAD	8.3 min
EXPANSION SLOTS	(1) Mini-Slot (MS) expansion port with Gigabit Network Card (NETWORK-M3) included
ETHERNET INTERFACE	Yes
INCLUDES NETWORK CARD	Yes
SOFTWARE COMPATIBILITY	Brightlayer Data Centers suite
USER INTERFACE	Graphical display, 5-button programmable menu, LED indicator
ALTITUDE	3000 m
BTU RATING	Online: 767 BTU/hr, Battery: 1155 BTU/hr, High Efficiency: 205 BTU/hr
NOISE LEVEL	<43 dB at 1 meter
RELATIVE HUMIDITY	0-95% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
PROTOCOL	SNMP
EFFICIENCY AT MAX. LOAD	96%
MAX NUMBER OF BATTERY PACKS	12
OUTPUT FREQUENCY	50/60 Hz
OUTPUT POWER FACTOR	0.9 (240V L6-30P), 1.0 (hardwired input)
OUTPUT VOLTAGE RANGE	±1% steady-state
RUNTIME AT FULL LOAD	3 min. (5400W)
OUTPUT CAPACITY DETAILS	240V: 5400 watts (L6-30P input); 230V: 5300 watts (L6-30P input); 220V: 5100 watts (L6-30P input); 208V: 4800 watts (L6-30P input); 200V: 4600 watts (L6-30P input); 200V - 240V: 6000 watts (hardwired UPS input)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

FECHA:



Eaton Corporation plc

Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. Todos los derechos reservados.