

Especificaciones

Eaton 9PX11KG2



Eaton 9PX Gen 2 UPS, 11000 VA, 11000 W,
Input: Hardwired, Outputs: Hardwired, (4)
L6-30R, 4U Rack/tower, VRLA battery, Gigabit
Network card included



General specifications

PRODUCT NAME	Eaton 9PX UPS
CATALOG NUMBER	9PX11KG2
UPC	786689860059
PRODUCT LENGTH/DEPTH	28.5 in
PRODUCT HEIGHT	6.85 in
PRODUCT WIDTH	17.32 in
PRODUCT WEIGHT	173.72 lb
COMPLIANCES	CISPR22 Class A / FCC part 15 Class A CE Marked FCC Part 15
CERTIFICATIONS	IEC 62040-2:2006 Cat C2 cULus Listed NOM ENERGY STAR certified ICC-ES AC156 OSHPD Seismic certified

Especificaciones del producto

Recursos

SPECIAL FEATURES	Gigabit Network Card (NETWORK-M3) included
TOPOLOGY	Online/Double-conversion
FORM FACTOR	Rack/tower
RACK SIZE	4U
COLOR	Black/silver
VA RATING	11 kVA
WATTAGE	11 kW
RACK MOUNTING KIT	Yes

PACKAGE CONTENTS

- 11000VA 11000W 9PX G2 Online Double-Conversion UPS
- NETWORK-M3 Gigabit network card
- USB cable
- RS-232 cable
- Cable gland for hardwire connection
- Rack-mounting hardware
- Tower support stands
- Quick Start Guide

SURGE PROTECTION	Yes
INTERNAL BYPASS	Yes
INPUT CONNECTION	Hardwired
INPUT NOMINAL VOLTAGE	208V default (200/208/220/230/240V)
INPUT FREQUENCY RANGE	60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz
INPUT POWER FACTOR	>0.99 typical
RECEPTACLE	(4) L6-30R, Hardwired
NUMBER OF OUTPUTS L6-30R	4
OUTPUT WAVEFORM	True sine wave
VOLTAGE	208 V
OUTPUT NOMINAL VOLTAGE	208V default (200/208/220/230/240/250V)
RUNTIME GRAPH	\$row.attributeValue.cdata
BATTERY MANAGEMENT	ABM+ technology uses battery replacement analytics to predict when you should replace UPS batteries based on real-life

	usage and conditions.
BATTERY REPLACEMENT	Hot-swappable internal batteries and extended battery modules (EBMs). Replacement battery part # EBP-2003 (qty 2 per UPS)
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	Add up to 12 EBMs, part # 9PXEBM240RTG2
STANDARD FACTORY WARRANTY	<ul style="list-style-type: none"> • 3-YEAR FACTORY WARRANTY • - 3 years • - Parts, electronics and batteries coverage • - Standard ground shipping • - Technical support
EXTENDED SERVICE PLANS	<ul style="list-style-type: none"> • ADVANCED DEPOT EXCHANGE • - 5-year depot repair: 9SW5Y-11000UC • - Expedited parts coverage for 5 years • - Parts, electronics and UPS batteries coverage • - Next business day shipping • - Technical support • • 5-YEAR ON-SITE PLAN: WFLN75XX-11000UC • - On-site parts and labor coverage for years 5 • - Parts, electronics and UPS batteries coverage • - 24x7 on-site labor coverage, next-day response • - Next-day shipping • - Technical support
RUNTIME AT HALF LOAD	9.4 min
EXPANSION SLOTS	(2) Mini-Slot (MS) expansion ports with 1 Gigabit Network Card (NETWORK-M3) included

ETHERNET INTERFACE	Yes
INCLUDES NETWORK CARD	Yes
SOFTWARE COMPATIBILITY	Brightlayer Data Centers suite
USER INTERFACE	Graphical display, 5-button programmable menu, LED indicator
ALTITUDE	3000 m
BTU RATING	Online: 1160 BTU/hr, Battery: 1767 BTU/hr, High Efficiency: 188 BTU/hr
NOISE LEVEL	<43 dB at 1 meter
RELATIVE HUMIDITY	0-95% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
PROTOCOL	SNMP
EFFICIENCY AT MAX. LOAD	97%
MAX NUMBER OF BATTERY PACKS	12
OUTPUT FREQUENCY	50/60 Hz
OUTPUT POWER FACTOR	1.0
OUTPUT VOLTAGE RANGE	±1% steady-state
RUNTIME AT FULL LOAD	3.1 min. (11000W)

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
FECHA:



Eaton Corporation plc
Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

Follow us on social media to get the latest product and support information.

