



# MWE GOLD 750 V3

## ATX 3.1 White Edition

### Non-Modular

Introducing the MWE Gold V3, the evolutionary next step in Cooler Master power and the ATX 3.1 upgrade to our G Gold PSU. With features such as 80 Plus Gold efficiency, a DC-to-DC + LLC circuit design, and a quiet HDB fan cooling, the V3 provides valuable performance in multiple dimensions.

Several changes and additions improve the overall user experience. Together, these design choices deliver an advanced PSU that is highly efficient and reliable. With an embossed cable, exceptional temperature resilience and a 5-year warranty, the MWE Gold V3 will evolve your machine.

## FEATURES

### **Quiet HDB fan**

A hydrodynamic bearing fan delivers long-lasting quiet and effective cooling.

### **80 Plus Gold efficiency certification**

This unit is certified to achieve more than 90% efficiency at typical loads in a 115V test.

### **High temperature resilience**

A 40°C maximum operating temperature allows for pushing your machine to the limits with overclocking and other high-intensity applications.

### **Embossed cable**

An embossed cable texture provides a softer and overall improved grip with a pleasing aesthetic.

### **ATX 3.1 support & a durable 12V-2x6 cable**

The ATX 3.1-compliant power supply supports 200% Times the peak power, making it ideal for next-generation series GPUs to easily meet the demands of future high-performance graphics cards. Includes 180-degree 12+4pin (12V-2x6) cable that can support the maximum power consumption of 450W for mainstream graphics cards.

### **Single +12V rail**

All power comes from a single +12V source, ensuring consistent output through all connected cables.

### **DC-to-DC technology**

The DC-DC circuit design offers reliable, stable output to all connected components.

### **2 EPS Connectors**

Two 4-pin EPS connectors are included for universal compatibility with current-gen motherboards.

### **5-year warranty**

This unit comes with a standard limited manufacturing warranty of 5 years from the date of purchase.



# SPECIFICATIONS

<b>Product Name</b>	MWE GOLD 750 V3 ATX 3.1 White Edition Non-Modular	
<b>Product Number</b>	MPE-7506-ACAG-G**	
<b>ATX Version</b>	ATX 12V Ver. 3.1	
<b>PFC</b>	Active PFC	
<b>Input Voltage</b>	100 – 240V	
<b>Input Current</b>	10 – 6A	
<b>Input Frequency</b>	50 – 60Hz	
<b>Dimension (L x W x H)</b>	140 x 150 x 86 mm	
<b>Fan Size</b>	120mm	
<b>Fan Bearing</b>	HDB	
<b>Fan Speed</b>	2400 RPM	
<b>Efficiency</b>	≥ 90% @ Typical Load	
<b>80 PLUS Rating</b>	80 PLUS Gold	
<b>ErP 2014 Lot 3</b>	Yes	
<b>Operating Temperature</b>	0 ~ 40°C	
<b>Power Good Signal</b>	100 – 150ms	
<b>Hold Up Time</b>	≥ 16ms @ 80% Load	
<b>MTBF</b>	>100,000 hours	
<b>Protections</b>	UVP / OVP / OPP / OTP / SCP / OCP	
<b>Regulatory</b>	cTUVus, TUV, CE, FCC, BSMI, CCC, EAC, RCM, UKCA, RoHS2.0 / BIS, KC (based on region's request.)	
<b>Connectors</b>	ATX 24 Pin	x1 = 1x (550mm)
	EPS 8 Pin / 4+4 Pin	x2 = 1x (550+120mm)
	PCI-e 6+2 Pin	x4 = 2x (550+120mm)
	SATA	x6 = 2x (400+150+150mm)
	Peripheral 4 Pin	x3 = 1x (400+150+150mm)
	12V-2x6 (12+4 Pin)	x1 = 1x (600mm)



Make It Yours

AC INPUT	100 - 240V~, 10 - 6A, 50 - 60Hz				
DC OUTPUT	+3.3V	+5V	+12V	-12V	+5Vsb
	20A	20A	62.5A	0.3A	3A
TOTAL POWER	100W		750W	3.6W	15W
			750W		

## SHIPPING DETAILS

Net Weight	1800g	
Gross Weight	2210g	
Packaging dimension (L x W x H)	260 x 190 x110mm	
Carton Dimension (L x W x H)	57 x 27.5 x 21.5 cm / 22.44 x 10.83 x 8.46 inch	
Unit / Pallet	120pcs	
Container 20 feet	With Pallet	2400pcs
	Carton / Pallet	24pcs
	Without Pallet	/
Container 40 feet	With Pallet	5280pcs
	Carton / Pallet	24pcs
	Without Pallet	/
Container 40 HQ	With Pallet	5280pcs
	Carton / Pallet	24pcs
	Without Pallet	/