

## THE NEW GENERATION SNMP CARD WITH ALL NEW DESIGNED DIMENSION FOR UPS AND OTHER EQUIPMENT

NetAgent Mini integrates multi-network communication protocols to enable a comprehensive, easy-to understand and secure remote monitoring and management for UPS and other equipment via the Internet.



# *NetAgent Mini*

### **Mega Tec Net Agent Mini DP520**

#### **Ventajas:**

- Dimensiones reducidas.
- Variedad de protocolos de red soportados: Windows, Linux, Mac, etc.
- Sistema autónomo embebido. Permite operación sin computadora personal.
- Soporta protocolos de comunicación multi-red.
- Acceso basado en internet para facilitar el monitoreo y control de UPS.
- 10M/100M Ethernet auto-detectado.

#### **UPS Soportados:**

- Soporta protocolos Mega Tec /SEC
- Soporta 1 o 3 fases.

#### **Sistema de notificaciones:**

- Notificaciones TRAP
- Notificaciones SNMP por correo electrónico sin requerir PC.

#### **Software incluido:**


- SNMPView, Simple NMS, soporta todas las versiones Windows desde XP.
- Multi-Mon permite el monitoreo de múltiples UPS.
- ClientMate: Software SNMP de apagado ordenado para todos los sistemas operativos Windows.
- Utilería Multi-monitoreo.

#### **Protocolos de red soportados:**

- Soporta protocolos multi-red y aplicaciones TCP/IP como SNMP, HTTP, Telnet, E-mail SMTP, SNTP, PPP, DNS, DHCP, PDA etc.

#### **Sistemas de Notificación soportados:**

- HP OpenView.
- Sun SunNet Manager.
- IBM Trivoli.
- Novell NMS.
- Mega Tec SNMPView.
- Otros compatibles a SNMP.



Product Number	DP520	DK520a	DK521	DK530
CPU	ARM 50 MHz 32Bit			
System Clock	25MHz/50MHz			
Port	1 Port			
Flash Memory	1MB			
SDRAM	8MB			
Web Multi-Language	Yes			
LED	6			
Power Supply	4.5V ~ 7V DC, 250mA Max			
Ethernet Throughput	808 Kbytes Pre Seconds			
Ethernet Latency	0.89 Milliseconds			
Operating Voltage	3.3 Volt			
Watch Dog	Hardware Watch Dog			
LAN interface	10M/100M UTP			
LAN Protocol	TCP/IP, , HTTP, SMTP, SNMP, DHCP, Telnet, BOOTP, DNS, DDNS, PPPoE, Wap, PDA browser, SNMP RFC1628 MIB, PPC MIB Ethernet Upgrade firmware			
Contact closure UPS			<input type="radio"/>	<input type="radio"/>
MegaTec Protocol	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
MegaTec 3 Phase Protocol	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
PhoenixTec Protocol	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
SEC Protocol	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
External Box			<input type="radio"/>	<input type="radio"/>
Internal Card / Module	<input type="radio"/>	<input type="radio"/>		<input type="radio"/>
LCD Panel				<input type="radio"/>
Dimension (mm)	63x48x25	63x48x25	63x48x21	63x48x21
Weight (g)	50	50	70	75
Connector	4 Pins Wafer connector	7 Pins Wafer connector	9 Pins D-SUB Connector	9 Pins D-SUB Connector
Picture				

